

All louvers shown meet some or all Florida and International Building Code Requirements for the hurricane-prone region.

Model Name Max. Wind-load	Construction Description Dimensions – inches (mm)	500-L AMCA Certifications	AMCA Listed	Miami-Dade County, FL NOA No.	Florida Product Approved No.	Florida Test Protocols	Minimum Opening	Maximum Section	Maximum Opening
							Dimensions – inches (mm)		
Miami-Dade Approved Louvers									
1606DHPM	6" (152) deep, extruded aluminum stationary louver with high performance horizontal drainable blades	Water, Air	AMCA 540 Enhanced Level E AMCA 550 (with optional 2020 damper in closed position)	23-0724.23 EXP. 08-30-2028	28078.3		12 W x 12 H (305 x 305)	72 W x 120 H (1829 x 3048)	Unlimited Width x 120 H (Unlimited Width x 3048 H)
150 PSF									
1606CM	6" (152) deep, extruded aluminum combination horizontal blade louver / airfoil blade damper		AMCA 540 Basic Level D AMCA 550 (with blades closed)	23-0823.04 EXP. 11-2-2028	41947.2		12 W x 16 H (305 x 406)	60 W x 120 H (1524 x 3048)	
120 PSF									
1605WDM	5" (127) deep, extruded aluminum stationary louver with wind-driven rain resistant horizontal blades		AMCA 540 Enhanced Level E AMCA 550 (with optional 2020 damper in closed position)	23-0724.24 EXP. 08-30-2028	28078.1			72 W x 120 H (1829 x 3048)	
150 PSF									
1609HM	9" (229) deep, extruded aluminum stationary hybrid with wind-driven rain resistant louver horizontal front and rear vertical blades	Water, Air, & Wind Driven Rain		23-0823.05 EXP. 04-04-2024	41947.1		12 W x 12 H (305 x 305)	60 W x 120 H (1524 x 3048)	
160 PSF									
1605WDVM	5" (127) deep, extruded aluminum stationary louver with wind-driven rain resistant vertical blades		AMCA 540 Enhanced Level E AMCA 550	23-0724.25 EXP. 08-30-2028	28078.2			72 W x 120 H or 120 W x 72 H (1829 x 3048 or 1829 x 3048)	
130 PSF									
1675WDVM	5" (127) deep, extruded aluminum stationary louver with wind-driven rain resistant vertical blades			23-0724.22 EXP. 08-30-2028	28078.4			48 W x 120 H or 120 W x 48 H (1219 x 3048 or 3049 x 1219)	
150 PSF									

Model Name Max. Wind-load	Construction Description Dimensions – inches (mm)	500-L AMCA Certifications	AMCA Listed	Miami-Dade County, FL NOA No.	Florida Product Approved No.	Florida Test Protocols	Minimum Opening	Maximum Section	Maximum Opening				
							Dimensions – inches (mm)						
Florida Product Approved Louvers													
1604DHPF* Up to 55 PSF †	4" (102) deep, extruded aluminum stationary louver with high performance drainable blade	Water, Air	AMCA 540 Basic Level D	N/A	19273.1	TAS-201 TAS-202 TAS-203	12 W x 12 H (305 x 305)	48 W x 120 H or 120 W x 48 H (1219 x 3048 or 3049 x 1219)	40 sq. ft. (3.7 m2). Larger louvers require field assembly of smaller sections.				
1606DHPF* Up to 150 PSF †	6 in. (152) deep, extruded aluminum with horizontal drainable blade louver		AMCA 540 Enhanced Level E AMCA 550 (with optional 2020 damper in closed position)					19273.4					
1605WDF* Up to 150 PSF †	5" (127) deep extruded aluminum stationary louver with wind-driven rain resistant horizontal blade	Water, Air & Wind Driven Rain	AMCA 540 Enhanced Level E AMCA 550					19273.2	108 W x 84 H or 84 W x 120 H (2743 x 2134 or 2134 x 2743)	Unlimited Width x 120 H (Unlimited Width x 3048 H)			
1606WDF* Up to 150 PSF †	6" (152) deep extruded aluminum stationary louver with wind-driven rain resistant horizontal blade							19273.5					
1605WDVF* Up to 130 PSF †	5" (127) deep extruded aluminum stationary louver with high velocity wind-driven rain resistant vertical blade							19273.3			72 W x 120 H or 120 W x 72 H (1829 x 3048 or 1829 x 3048)		
AMCA 540 & AMCA 550 Listed Louvers													
1606C	6" (152) Deep, extruded aluminum combination louver/damper with high velocity wind-driven rain and impact resistant vertical blade	Water, Air	AMCA 540 Basic Level D AMCA 550 (with blades closed)					N/A	12 W x 16 H (305 x 406)	12 W x 12 H (305 x 305)	60 W x 120 H (1524 x 3048)	72 W x 120 H or 120 W x 72 H (1829 x 3048 or 1829 x 3048)	Unlimited Width x 120 H (Unlimited Width x 3048 H)
1609H	9" (229) deep, extruded aluminum stationary hybrid louver with high velocity wind-driven rain and impact resistant horizontal and vertical blade	Water, Air & Wind Driven Rain	AMCA 540 Enhanced Level E AMCA 550										
1605WDV	5" (127) deep, extruded aluminum stationary louver with high velocity wind-driven rain and impact resistant vertical blade												

* Also available in architectural shapes. Contact factory.

† Size and Section dependent