

All louvers shown meet some or all Florida and International Building Code Requirements for the hurricane-prone region.

| Model Name<br>Max.<br>Wind-load | Construction Description<br>Dimensions – inches (mm)                                                                                      | 500-L AMCA<br>Certifications             | AMCA<br>Listed                                                                                | Miami-Dade<br>County, FL<br>NOA No. | Florida<br>Product<br>Approved<br>No.                              | Florida<br>Test<br>Protocols  | Minimum<br>Opening         | Maximum<br>Section            | Maximum<br>Opening                                          |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|-----------------------------------------------------------------------------------------------|-------------------------------------|--------------------------------------------------------------------|-------------------------------|----------------------------|-------------------------------|-------------------------------------------------------------|
|                                 |                                                                                                                                           |                                          |                                                                                               |                                     |                                                                    |                               | Dimensions – inches (mm)   |                               |                                                             |
| Miami-Dade Approved Louvers     |                                                                                                                                           |                                          |                                                                                               |                                     |                                                                    |                               |                            |                               |                                                             |
| <a href="#">1606DHPM</a>        | 6" (152) deep, extruded aluminum stationary louver<br>with high performance horizontal drainable blades                                   | Water, Air                               | AMCA 540<br>Enhanced Level E<br>AMCA 550<br>(with optional 2020 damper in<br>closed position) | 24-0516.04<br>EXP. 08-30-2028       | 41441.3                                                            | TAS-201<br>TAS-202<br>TAS-203 | 12 W x 12 H<br>(305 x 305) | 72 W x 120 H<br>(1829 x 3048) | Unlimited<br>Width x 120 H<br>(Unlimited<br>Width x 3048 H) |
| 150 PSF                         |                                                                                                                                           |                                          |                                                                                               |                                     |                                                                    |                               |                            |                               |                                                             |
| <a href="#">1606CM</a>          | 6" (152) deep, extruded aluminum combination<br>horizontal blade louver / airfoil blade damper                                            |                                          | AMCA 540<br>Basic Level D<br>AMCA 550<br>(with blades closed)                                 | 23-0823.04<br>EXP. 11-2-2028        | 41947.2                                                            |                               | 12 W x 16 H<br>(305 x 406) | 60 W x 120 H<br>(1524 x 3048) |                                                             |
| 120 PSF                         |                                                                                                                                           |                                          |                                                                                               |                                     |                                                                    |                               |                            |                               |                                                             |
| <a href="#">1605WDM</a>         | 5" (127) deep, extruded aluminum stationary louver<br>with wind-driven rain resistant horizontal blades                                   | Water, Air,<br>&<br>Wind Driven Rain     | AMCA 540<br>Enhanced Level E<br>AMCA 550<br>(with optional 2020 damper in<br>closed position) | 24-0516.05<br>EXP. 08-30-2028       | 41441.1                                                            |                               | 12 W x 12 H<br>(305 x 305) | 72 W x 120 H<br>(1829 x 3048) |                                                             |
| 150 PSF                         |                                                                                                                                           |                                          |                                                                                               |                                     |                                                                    |                               |                            |                               |                                                             |
| <a href="#">1609HM</a>          | 9" (229) deep, extruded aluminum stationary hybrid<br>with wind-driven rain resistant louver horizontal front<br>and rear vertical blades |                                          | AMCA 540<br>Enhanced Level E<br>AMCA 550                                                      | 23-0823.05<br>EXP. 04-04-2029       | 41947.1                                                            |                               |                            | 60 W x 120 H<br>(1524 x 3048) |                                                             |
| 160 PSF                         |                                                                                                                                           |                                          |                                                                                               |                                     |                                                                    |                               |                            |                               |                                                             |
| <a href="#">1605WDVM</a>        | 5" (127) deep, extruded aluminum stationary louver<br>with wind-driven rain resistant vertical blades                                     | AMCA 540<br>Enhanced Level E<br>AMCA 550 | 24-0516.06<br>EXP. 08-30-2028                                                                 | 41441.2                             | 72 W x 120 H or<br>120 W x 72 H<br>(1829 x 3048 or<br>1829 x 3048) |                               |                            |                               |                                                             |
| 130 PSF                         |                                                                                                                                           |                                          |                                                                                               |                                     |                                                                    |                               |                            |                               |                                                             |
| <a href="#">1675WDVM</a>        | 5" (127) deep, extruded aluminum stationary louver<br>with wind-driven rain resistant vertical blades                                     | AMCA 540<br>Enhanced Level E<br>AMCA 550 | 24-0516.03<br>EXP. 08-30-2028                                                                 | 41441.4                             | 48 W x 120 H or<br>120 W x 48 H<br>(1219 x 3048 or<br>3049 x 1219) |                               |                            |                               |                                                             |
| 150 PSF                         |                                                                                                                                           |                                          |                                                                                               |                                     |                                                                    |                               |                            |                               |                                                             |

| Model Name<br>Max.<br>Wind-load    | Construction Description<br>Dimensions – inches (mm)                                                                                             | 500-L AMCA<br>Certifications        | AMCA<br>Listed                                                                                                 | Miami-Dade<br>County, FL<br>NOA No. | Florida<br>Product<br>Approved<br>No.    | Florida<br>Test<br>Protocols             | Minimum<br>Opening         | Maximum<br>Section                                                 | Maximum<br>Opening                                                                       |                                          |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|----------------------------------------------------------------------------------------------------------------|-------------------------------------|------------------------------------------|------------------------------------------|----------------------------|--------------------------------------------------------------------|------------------------------------------------------------------------------------------|------------------------------------------|
|                                    |                                                                                                                                                  |                                     |                                                                                                                |                                     |                                          |                                          | Dimensions – inches (mm)   |                                                                    |                                                                                          |                                          |
| Florida Product Approved Louvers   |                                                                                                                                                  |                                     |                                                                                                                |                                     |                                          |                                          |                            |                                                                    |                                                                                          |                                          |
| <a href="#">1604DHPF*</a>          | 4" (102) deep, extruded aluminum stationary louver with high performance drainable blade                                                         | Water, Air                          | AMCA 540<br>Basic Level D                                                                                      | N/A                                 | 19273.1                                  | TAS-201<br>TAS-202<br>TAS-203            | 12 W x 12 H<br>(305 x 305) | 48 W x 120 H or<br>120 W x 48 H<br>(1219 x 3048 or<br>3049 x 1219) | 40 sq. ft. (3.7 m2).<br>Larger louvers require<br>field assembly of<br>smaller sections. |                                          |
| Up to 55 PSF †                     |                                                                                                                                                  |                                     | AMCA 540<br>Enhanced Level E<br>AMCA 550<br>(with optional 2020 damper in<br>closed position)                  |                                     | 19273.4                                  |                                          |                            | 108 W x 84 H or<br>84 W x 120 H<br>(2743 x 2134 or<br>2134 x 2743) | Unlimited<br>Width x 120 H<br>(Unlimited<br>Width x 3048 H)                              |                                          |
| <a href="#">1606DHPF*</a>          | 6 in. (152) deep, extruded aluminum with horizontal drainable blade louver                                                                       | Water, Air<br>&<br>Wind Driven Rain |                                                                                                                |                                     |                                          |                                          |                            |                                                                    |                                                                                          | 19273.2                                  |
| Up to 150 PSF †                    |                                                                                                                                                  |                                     | 5" (127) deep extruded aluminum stationary louver with wind-driven rain resistant horizontal blade             |                                     | AMCA 540<br>Enhanced Level E             |                                          |                            |                                                                    |                                                                                          |                                          |
| <a href="#">1605WDF*</a>           | 6" (152) deep extruded aluminum stationary louver with wind-driven rain resistant horizontal blade                                               | Water, Air                          |                                                                                                                |                                     |                                          |                                          |                            |                                                                    |                                                                                          | AMCA 540<br>Enhanced Level E<br>AMCA 550 |
| Up to 150 PSF †                    |                                                                                                                                                  |                                     | 5" (127) deep extruded aluminum stationary louver with high velocity wind-driven rain resistant vertical blade |                                     | Water, Air                               |                                          |                            |                                                                    |                                                                                          |                                          |
| <a href="#">1606WDF*</a>           | 6" (152) deep extruded aluminum stationary louver with wind-driven rain resistant horizontal blade                                               | Water, Air                          |                                                                                                                |                                     |                                          |                                          |                            |                                                                    |                                                                                          | AMCA 540<br>Enhanced Level E<br>AMCA 550 |
| Up to150 PSF †                     |                                                                                                                                                  |                                     | 5" (127) deep extruded aluminum stationary louver with high velocity wind-driven rain resistant vertical blade | Water, Air                          | AMCA 540<br>Enhanced Level E<br>AMCA 550 |                                          |                            |                                                                    |                                                                                          |                                          |
| <a href="#">1605WDVF*</a>          | 5" (127) deep extruded aluminum stationary louver with high velocity wind-driven rain resistant vertical blade                                   | Water, Air                          |                                                                                                                |                                     |                                          | AMCA 540<br>Enhanced Level E<br>AMCA 550 |                            |                                                                    |                                                                                          |                                          |
| Up to 130 PSF †                    |                                                                                                                                                  |                                     | 5" (127) deep extruded aluminum stationary louver with high velocity wind-driven rain resistant vertical blade | Water, Air                          | AMCA 540<br>Enhanced Level E<br>AMCA 550 |                                          |                            |                                                                    |                                                                                          |                                          |
| AMCA 540 & AMCA 550 Listed Louvers |                                                                                                                                                  |                                     |                                                                                                                |                                     |                                          |                                          |                            |                                                                    |                                                                                          |                                          |
| <a href="#">1606C</a>              | 6" (152) deep, extruded aluminum combination louver/ damper with high velocity wind-driven rain and impact resistant vertical blade              | Water, Air                          | AMCA 540<br>Basic Level D<br>AMCA 550<br>(with blades closed)                                                  | N/A                                 |                                          |                                          | 12 W x 16 H<br>(305 x 406) | 60 W x 120 H<br>(1524 x 3048)                                      | Unlimited<br>Width x 120 H<br>(Unlimited<br>Width x 3048 H)                              |                                          |
| <a href="#">1609H</a>              | 9" (229) deep, extruded aluminum stationary hybrid louver with high velocity wind-driven rain and impact resistant horizontal and vertical blade | Water, Air<br>&<br>Wind Driven Rain | AMCA 540<br>Enhanced Level E<br>AMCA 550                                                                       |                                     |                                          |                                          | 12 W x 12 H<br>(305 x 305) |                                                                    |                                                                                          |                                          |
| <a href="#">1603WDV</a>            | 3" (76) deep, extruded aluminum stationary louver with high velocity wind-driven rain and impact resistant vertical blade                        |                                     | AMCA 540<br>Basic Level D<br>AMCA 550                                                                          |                                     |                                          |                                          |                            |                                                                    |                                                                                          |                                          |
| <a href="#">1605WDV</a>            | 5" (127) deep, extruded aluminum stationary louver with high velocity wind-driven rain and impact resistant vertical blade                       |                                     | AMCA 540<br>Enhanced Level E<br>AMCA 550                                                                       |                                     |                                          |                                          |                            |                                                                    |                                                                                          |                                          |

\* Also available in architectural shapes. Contact factory.

† Size and Section dependent