

All louvers shown meet some or all Florida and International Building Code Requirements for the hurricane-prone region.

Model Name Max. Wind-load	Construction Description Dimensions – inches (mm)	500-L AMCA Certifications	AMCA Listed	Miami-Dade County, FL NOA No.	Florida Product Approved No.	Florida Test Protocols	Minimum Opening	Maximum Section	Maximum Opening
							Dimensions – inches (mm)		
Miami-Dade Approved Louvers									
1606DHPM	6" (152) deep, extruded aluminum stationary louver with high performance horizontal drainable blades	Water, Air	AMCA 540 Enhanced Level E AMCA 550 (with optional 2020 damper in closed position)	24-0516.04 EXP. 08-30-2028	41441.3	TAS-201 TAS-202 TAS-203	12 W x 12 H (305 x 305)	72 W x 120 H (1829 x 3048)	Unlimited Width x 120 H (Unlimited Width x 3048 H)
150 PSF									
1606CM	6" (152) deep, extruded aluminum combination horizontal blade louver / airfoil blade damper		AMCA 540 Basic Level D AMCA 550 (with blades closed)	23-0823.04 EXP. 11-2-2028	41947.2		12 W x 16 H (305 x 406)	60 W x 120 H (1524 x 3048)	
120 PSF									
1605WDM	5" (127) deep, extruded aluminum stationary louver with wind-driven rain resistant horizontal blades	AMCA 540 Enhanced Level E AMCA 550 (with optional 2020 damper in closed position)	24-0516.05 EXP. 08-30-2028	41441.1	12 W x 12 H (305 x 305)		72 W x 120 H (1829 x 3048)		
150 PSF									
1609HM	9" (229) deep, extruded aluminum stationary hybrid with wind-driven rain resistant louver horizontal front and rear vertical blades	AMCA 540 Enhanced Level E AMCA 550	23-0823.05 EXP. 04-04-2029	41947.1			60 W x 120 H (1524 x 3048)		
160 PSF									
1605WDVM	5" (127) deep, extruded aluminum stationary louver with wind-driven rain resistant vertical blades		24-0516.06 EXP. 08-30-2028	41441.2	72 W x 120 H or 120 W x 72 H (1829 x 3048 or 1829 x 3048)				
130 PSF									
1675WDVM	5" (127) deep, extruded aluminum stationary louver with wind-driven rain resistant vertical blades	24-0516.03 EXP. 08-30-2028	41441.4	48 W x 120 H or 120 W x 48 H (1219 x 3048 or 3049 x 1219)					
150 PSF									

Model Name Max. Wind-load	Construction Description Dimensions – inches (mm)	500-L AMCA Certifications	AMCA Listed	Miami-Dade County, FL NOA No.	Florida Product Approved No.	Florida Test Protocols	Minimum Opening	Maximum Section	Maximum Opening
							Dimensions – inches (mm)		
Florida Product Approved Louvers									
1604DHPF*	4" (102) deep, extruded aluminum stationary louver with high performance drainable blade	Water, Air	AMCA 540 Basic Level D	N/A	19273.1	TAS-201 TAS-202 TAS-203	12 W x 12 H (305 x 305)	48 W x 120 H or 120 W x 48 H (1219 x 3048 or 3049 x 1219	40 sq. ft. (3.7 m2). Larger louvers require field assembly of smaller sections.
Up to 55 PSF †									
1606DHPF*	6 in. (152) deep, extruded aluminum with horizontal drainable blade louver	AMCA 540 Enhanced Level E AMCA 550 (with optional 2020 damper in closed position)	19273.4		108 W x 84 H or 84 W x 120 H (2743 x 2134 or 2134 x 2743)			Unlimited Width x 120 H (Unlimited Width x 3048 H)	
Up to 150 PSF †									
1605WDF*	5" (127) deep extruded aluminum stationary louver with wind-driven rain resistant horizontal blade	Water, Air & Wind Driven Rain	19273.2						
Up to 150 PSF †									
1606WDF*	6" (152) deep extruded aluminum stationary louver with wind-driven rain resistant horizontal blade	AMCA 540 Enhanced Level E	19273.5						
Up to 150 PSF †									
1605WDVF*	5" (127) deep extruded aluminum stationary louver with high velocity wind-driven rain resistant vertical blade	Water, Air	AMCA 540 Enhanced Level E AMCA 550	19273.3		72 W x 120 H or 120 W x 72 H (1829 x 3048 or 1829 x 3048			
Up to 130 PSF †									
AMCA 540 & AMCA 550 Listed Louvers									
1606C	6" (152) deep, extruded aluminum combination louver/ damper with high velocity wind-driven rain and impact resistant vertical blade	Water, Air	AMCA 540 Basic Level D AMCA 550 (with blades closed)	N/A			12 W x 16 H (305 x 406)	60 W x 120 H (1524 x 3048)	Unlimited Width x 120 H (Unlimited Width x 3048 H)
1605H	5" (127) deep, extruded aluminum stationary hybrid louver with high velocity wind-driven rain and impact resistant horizontal and vertical blade	Water, Air & Wind Driven Rain	AMCA 540 Enhanced Level E AMCA 550				12 W x 12 H (305 x 305)		
1609H	9" (229) deep, extruded aluminum stationary hybrid louver with high velocity wind-driven rain and impact resistant horizontal and vertical blade		AMCA 540 Enhanced Level E AMCA 550						
1603WDV	3" (76) deep, extruded aluminum stationary louver with high velocity wind-driven rain and impact resistant vertical blade		AMCA 540 Basic Level D AMCA 550						
1605WDV	5" (127) deep, extruded aluminum stationary louver with high velocity wind-driven rain and impact resistant vertical blade		AMCA 540 Enhanced Level E AMCA 550						

* Also available in architectural shapes. Contact factory.

† Size and Section dependent