



EXTRUDED ALUMINUM STATIONARY LOUVER
4" (102) DEEP • K BLADE • DRAINABLE HEAD
MODEL: 1604KD

Model 1604KD, 4" (102) deep louver, combines good weather protection and performance with aesthetics that compliment any architecture. The design features a drainable head that collects the water running down the building face and channels it out the concealed downspouts in the side frame, thus preventing it from flowing down into the airstream. Suitable for use in exhaust and low to medium velocity intake applications, the K blade design features a rear water baffle plus an additional center rain hook, providing good protection against more forbidding weather conditions. Blades are reinforced with full length integral bosses for superior strength and the profile exhibits low pressure drop characteristics throughout the airflow range. Model 1604KD is available with channel or flanged type frame to suit most architectural and mechanical installation requirements.

STANDARD CONSTRUCTION:

- FRAME:** 4" (102) deep, Type 6063-T6 extruded aluminum, .080" (2.03) nominal wall thickness. Integral caulking slot provided.
- BLADES:** Type 6063-T6 extruded aluminum, .080" (2.03) nominal wall thickness, with reinforcing bosses. K style.
- BLADE ANGLE:** Fixed at 37 degrees.
- BLADE SPACING:** Approx. 4" (102) on centers.
- BLADE SUPPORT BRACKETS:** Concealed type, factory installed on rear of louver on maximum 60" (1524) centers. Reinforced with 1 1/2" x 2" (38 x 51) angle (adds approx. 2" [51] to overall louver depth).
- MULLIONS:** Concealed type allowing continuous line appearance up to 120" (3048) wide. Larger assemblies require separate visible frames with downspouts.
- SCREEN:** 3/4" x .051 (19 x 1.3) expanded, flattened aluminum bird screen in removable frame, inside (rear) mount (adds approximately 3/8" [10] to louver depth).
- FINISH:** Mill.
- MINIMUM SIZE:** 12" W x 12" H (305 x 305).
- MAX. SINGLE SECTION SIZE:** 120" W x 84" H (3048 x 2134) or 84" W x 120" H (2134 x 3048). 70 sq. ft. (6.5m²). Larger louvers will require field assembly of smaller sections.

OPTIONS:




- FL15** Flanged Frame, 1 1/2" (38).
- FL20** Flanged Frame, 2" (51).
- BSSS** Type 304 S.S. Bird Screen.
- BSN** No Bird Screen.
- ISA** Aluminum Insect Screen.
- ISSS** Type 304 S.S. Insect Screen.
- WE** Welded Construction.
- ESI** Extended Sill.
- FR1** 1" (25) Filter Rack.
- FR2** 2" (51) Filter Rack.
- PAC** Perimeter Anchor Clips.
- Other:** _____ .

OPTIONAL FINISHES:

- PC3** Powder Coat AAMA 2603. Color: _____ .
 - PC4** High Performance Powder Coat AAMA 2604 (Equivalent to 50% Kynar®). Color: _____ .
 - PC5** Fluoropolymer Powder Coat AAMA 2605 (Equivalent to 70% Kynar®). Color: _____ .
 - PCC** Prime Coat.
 - AN04** Clear Anodized 204-R1.
 - AN15** Clear Anodized 215-R1.
- Color Anodized:
- ANLB** Light Bronze. **ANMB** Medium Bronze.
 - ANDB** Dark Bronze. **ANBK** Black.

OPTIONAL W x H SIZING (1/4" [6.5] Undersize standard):

- U00** Exact Size.
- U38** Undersize 3/8" (9.5).
- U50** Undersize 1/2" (12.7).



OPT. FLANGED FRAME (FL15 STD.)

SCHEDULE TYPE:
PROJECT:
ENGINEER:
CONTRACTOR:

Page 1 of 3
Dimensions are in inches (mm).

DATE	B SERIES	SUPERSEDES	DRAWING NO.
4 - 22 - 24	1600	2 - 17 - 22	1604KD



**EXTRUDED ALUMINUM STATIONARY LOUVER
4" (102) DEEP • K BLADE • DRAINABLE HEAD
PERFORMANCE DATA
MODEL: 1604KD**

FREE AREA in Square Feet and Square Meters

		Width in Inches and Meters																		
		12	18	24	30	36	42	48	54	60	66	72	84	90	96	102	108	114	120	
		0.30	0.46	0.61	0.76	0.91	1.07	1.22	1.37	1.52	1.68	1.83	1.98	2.13	2.29	2.44	2.59	2.74	2.90	3.05
Height in Inches and Meters	12	0.21	0.34	0.47	0.60	0.73	0.85	0.98	1.11	1.24	1.37	1.49	1.62	1.75	1.88	2.01	2.13	2.26	2.39	2.52
	0.30	0.02	0.03	0.04	0.06	0.07	0.08	0.09	0.10	0.12	0.13	0.14	0.15	0.16	0.17	0.19	0.20	0.21	0.22	0.23
	18	0.46	0.74	1.02	1.30	1.58	1.86	2.14	2.41	2.69	2.97	3.25	3.53	3.81	4.09	4.37	4.64	4.92	5.20	5.48
	0.46	0.04	0.07	0.09	0.12	0.15	0.17	0.20	0.22	0.25	0.28	0.30	0.33	0.35	0.38	0.41	0.43	0.46	0.48	0.51
	24	0.73	1.17	1.60	2.04	2.48	2.91	3.35	3.79	4.22	4.66	5.10	5.53	5.97	6.41	6.85	7.28	7.72	8.16	8.59
	0.61	0.07	0.11	0.15	0.19	0.23	0.27	0.31	0.35	0.39	0.43	0.47	0.51	0.55	0.60	0.64	0.68	0.72	0.76	0.80
	30	0.93	1.49	2.05	2.61	3.17	3.74	4.30	4.86	5.42	5.98	6.54	7.10	7.66	8.22	8.78	9.34	9.90	10.46	11.02
	0.76	0.09	0.14	0.19	0.24	0.29	0.35	0.40	0.45	0.50	0.56	0.61	0.66	0.71	0.76	0.82	0.87	0.92	0.97	1.02
	36	1.15	1.85	2.54	3.23	3.93	4.62	5.31	6.00	6.70	7.39	8.08	8.77	9.47	10.16	10.85	11.54	12.24	12.93	13.62
	0.91	0.11	0.17	0.24	0.30	0.36	0.43	0.49	0.56	0.62	0.69	0.75	0.82	0.88	0.94	1.01	1.07	1.14	1.20	1.27
	42	1.40	2.24	3.08	3.93	4.77	5.61	6.45	7.29	8.13	8.97	9.81	10.66	11.50	12.34	13.18	14.02	14.86	15.70	16.54
	1.07	0.13	0.21	0.29	0.36	0.44	0.52	0.60	0.68	0.76	0.83	0.91	0.99	1.07	1.15	1.22	1.30	1.38	1.46	1.54
	48	1.62	2.59	3.56	4.53	5.50	6.48	7.51	8.42	9.39	10.36	11.33	12.30	13.28	14.25	15.22	16.19	17.16	18.13	19.10
	1.22	0.15	0.24	0.33	0.42	0.51	0.60	0.70	0.78	0.87	0.96	1.05	1.14	1.23	1.32	1.41	1.50	1.59	1.68	1.77
	54	1.84	2.95	4.06	5.16	6.27	7.37	8.48	9.58	10.69	11.80	12.90	14.01	15.11	16.22	17.33	18.43	19.54	20.64	21.75
	1.37	0.17	0.27	0.38	0.48	0.58	0.68	0.79	0.89	0.99	1.10	1.20	1.30	1.40	1.51	1.61	1.71	1.82	1.92	2.02
60	2.09	3.34	4.59	5.84	7.10	8.35	9.60	10.85	12.11	13.36	14.61	15.86	17.12	18.37	19.62	20.87	22.13	23.38	24.63	
1.52	0.19	0.31	0.43	0.54	0.66	0.78	0.89	1.01	1.12	1.24	1.36	1.47	1.59	1.71	1.82	1.94	2.06	2.17	2.29	
66	2.31	3.69	5.07	6.46	7.84	9.23	10.61	12.00	13.38	14.76	16.15	17.53	18.92	20.30	21.68	23.07	24.45	25.84	27.22	
1.68	0.21	0.34	0.47	0.60	0.73	0.86	0.99	1.11	1.24	1.37	1.50	1.63	1.76	1.89	2.01	2.14	2.27	2.40	2.53	
72	2.55	4.08	5.62	7.15	8.68	10.21	11.74	13.27	14.80	16.34	17.87	19.40	20.93	22.46	23.99	25.53	27.06	28.59	30.12	
1.83	0.24	0.38	0.52	0.66	0.81	0.95	1.09	1.23	1.38	1.52	1.66	1.80	1.94	2.09	2.23	2.37	2.51	2.66	2.80	
78	2.77	4.43	6.10	7.76	9.42	11.08	12.75	14.41	16.07	17.74	19.40	21.06	22.72	24.39	26.05	27.71	29.37	31.04	32.70	
1.98	0.26	0.41	0.57	0.72	0.88	1.03	1.18	1.34	1.49	1.65	1.80	1.96	2.11	2.27	2.42	2.57	2.73	2.88	3.04	
84	2.99	4.79	6.59	8.38	10.18	11.98	13.77	15.57	17.37	19.16	20.96	22.76	24.55	26.35	28.15	29.94	31.74	33.54	35.33	
2.13	0.28	0.45	0.61	0.78	0.95	1.11	1.28	1.45	1.61	1.78	1.95	2.11	2.28	2.45	2.61	2.78	2.95	3.12	3.28	
90	3.24	5.18	7.12	9.07	11.01	12.95	14.90	16.84	18.78	20.72	22.67	24.61	26.55							
2.29	0.30	0.48	0.66	0.84	1.02	1.20	1.38	1.56	1.74	1.93	2.11	2.29	2.47							
96	3.46	5.53	7.61	9.68	11.76	13.83	15.91	17.99	20.06	22.14	24.21	26.29	28.36							
2.44	0.32	0.51	0.71	0.90	1.09	1.29	1.48	1.67	1.86	2.06	2.25	2.44	2.63							
102	3.68	5.89	8.10	10.31	12.52	14.73	16.94	19.15	21.36	23.56	25.77	27.98	30.19							
2.59	0.34	0.55	0.75	0.96	1.16	1.37	1.57	1.78	1.98	2.19	2.39	2.60	2.80							
108	3.92	6.28	8.63	10.99	13.34	15.69	18.05	20.40	22.76	25.11	27.46	29.82	32.17							
2.74	0.36	0.58	0.80	1.02	1.24	1.46	1.68	1.90	2.11	2.33	2.55	2.77	2.99							
114	4.15	6.63	9.12	11.61	14.10	16.58	19.07	21.56	24.05	26.53	29.02	31.51	34.00							
2.90	0.39	0.62	0.85	1.08	1.31	1.54	1.77	2.00	2.23	2.46	2.70	2.93	3.16							
120	4.39	7.02	9.66	12.29	14.93	17.56	20.19	22.83	25.46	28.10	30.73	33.36	36.00							
3.05	0.41	0.65	0.90	1.14	1.39	1.63	1.88	2.12	2.37	2.61	2.85	3.10	3.34							

SCHEDULE TYPE:

PROJECT:

ENGINEER:

CONTRACTOR:

DATE

B SERIES

SUPERSEDES

DRAWING NO.

4 - 22 - 24

1600

2 - 17 - 22

1604KD




**EXTRUDED ALUMINUM STATIONARY LOUVER
4" (102) DEEP • K BLADE • DRAINABLE HEAD
PERFORMANCE DATA
MODEL: 1604KD**

**AIRFLOW/WATER PENETRATION DATA
for 48" x 48" (1219 x 1219) Louver Size**

	Free Area %	47%
	Free Area sq. ft. (sq. m.)	7.51 (0.70)
I N T A K E	Free Area Velocity at Point of Beginning Water Penetration at .01 oz./sq. ft. (3 ml/sq. m) (15 min. test duration)	892 fpm (272 m/min.)
	Air Volume at 892 fpm	6699 cfm (3161 l/s)
	Free Area Velocity	
	Pressure Drop @ 892 fpm	.11 in. w.g. (27 Pa)

NOTE: To minimize water penetration when sizing intake louvers, select a Free Area Velocity that is **below** the point of beginning water penetration.

PRESSURE DROP



Free Area Velocity (fpm)

Louver Test Size = 48" x 48" (1219 x 1219).
Pressure loss tested in accordance with Figure 5.5 of AMCA Standard 500-L. Data corrected to standard air density.

SCHEDULE TYPE:	Page 3 of 3			
PROJECT:	Dimensions are in inches (mm).			
ENGINEER:	DATE	B SERIES	SUPERSEDES	DRAWING NO.
CONTRACTOR:	4 - 22 - 24	1600	2 - 17 - 22	1604KD