



SINGLE DUCT TERMINAL UNIT
ACCESSORY • DISCHARGE SOUND ATTENUATOR
MODELS: AT303 AND AT305

Accessories:

Accessories ordered as separate standalone models.

AT Discharge Sound Attenuator (loose)

- 22 ga. (0.86) galvanized steel construction.
- Shipped loose for field attachment.
- Slip and drive connection.
- 3/4" (19) dual density fiberglass insulation, exposed edges coated to prevent erosion as standard.

- AT303** 3' (914) Long - Standard.
- AT305** 5' (1524) Long - Optional.
- Special Features: _____

Dimensional Data

Unit Size	W	H
4, 5, 6	10 (254)	10 (254)
7, 8	12 (305)	12 1/2 (318)
9, 10	14 (356)	12 1/2 (318)
12	18 (457)	12 1/2 (318)
14	24 (610)	12 1/2 (318)
16	28 (711)	12 1/2 (318)
24 x 16	38 (965)	18 (457)

Options:

- Steri-Liner.
- Fiber-Free Liner.
- Solid Metal Liner.
- 1" (25) Fiberglass Liner.
- 2" (51) Fiberglass Liner.
- Perforated Metal Liner.
- Steri-Liner with Perforated Liner.
- Access Door
 Sizes 4 to 12 : 8" x 5" (203 x 127) Flat Oval;
 Sizes 14 to 24 x 16: 12" x 6" (305 x 152) Flat Oval.
- Special Features: _____

Note: Select Insulation to match VAV terminal.

SCHEDULE TYPE:	Dimensions are in inches (mm)			
PROJECT:				
ENGINEER:	DATE	B SERIES	SUPERSEDES	DRAWING NO.
CONTRACTOR:	1 - 9 - 25	3000	3 - 30 - 17	30AT