

ALUMINUM CURVED SPIRAL DUCT GRILLES


TRUE FULL RADIUS DESIGN
DOUBLE DEFLECTION • ADJUSTABLE BLADES
MODELS: 51DHC AND 51DVC


■ MODEL 51DHC


Double Deflection Horizontal Front Blades


☐ MODEL 51DVC


Double Deflection Vertical Front Blades











Available Sizes

Grille Width	Grille	Duct Diameter
Min Max.	Height	Min Max.
10 - 48 (254 - 1219)	3 (76)	6 - 36 (152 - 914)
10 - 48 (254 - 1219)	4 (102)	6 - 36 (152 - 914)
10 - 48 (254 - 1219)	6 (152)	8 - 36 (203 - 914)
10 - 48 (254 - 1219)	8 (203)	10 - 36 (254 - 914)
10 - 48 (254 - 1219)	10 (254)	12 - 36 (305 - 914)
12 - 36 (305 - 914)	12 (305)	14 - 36 (356 - 914)

Duct diameters in even sizes only. Grilles available in nominal 1" (25) increments in width.

* Opening = Nominal + 1/4" (6) with DEX Damper/Extractor option.

Important:

Grilles are custom fabricated to fit only a single specified duct diameter.

DESCRIPTION:

- Nailor's unique curved spiral duct grille design offers an architecturally superior appearance and saves installation time and money by directly mounting to the duct and hence eliminating the need to fabricate standoff saddles for standard grilles.
- 2. Construction: Unique architectural single piece aluminum frame design is rolled to match required duct radius, eliminating unsightly non-aligned butted corners. Two sets of perpendicular extruded aluminum "teardrop" blades on 3/4" (19) centers provide air control in two planes. Individually adjustable blades are friction pivoted to ensure positive positioning when adjusted to desired deflection setting.
- 3. A thick foam gasket is provided as standard to ensure a tight seal to duct.
- 4. Standard fastening is Type A screw holes.
- 5. Standard finish is AW Appliance White.

Options:

- □ DEX Damper/Extractor* (Air scoop) (For supply air applications). Finish:
- □ AL Aluminum. □ MI Mill.
- ☐ SP Special. Specify _____

 SCHEDULE TYPE
 Dimensions are in inches (mm).

 PROJECT
 DATE
 B SERIES
 SUPERSEDES
 DRAWING NO.

 CONTRACTOR
 9 - 22 - 11
 5100C
 4 - 12 - 11
 5100C-2