


ALUMINUM FILTER RETURN GRILLES

EGGCRATE GRID CORE
45° DEFLECTION • SIGHTPROOF

MODEL: 51FE45

-	2 0 2.0.25 0.2		-
-	TYPE L = CEILING MC	DDULE - 1/4" (6)	-
		<u> </u>	

A = 2" (51) for 1" (25) filter. Standard. = 3" (76) for 2" (51) filter. Optional.



FRAME/BORDER:

- ☐ Type S Surface Mount
- ☐ Type L Lay-in T-Bar

DESCRIPTION:

- 1. Material: Extruded aluminum core and frame.
- 2. Provision for 1" (25) filter (by others) is standard.
- 3. Type S available in nominal sizes 6" x 4" (152 x 102) through 48" x 24" (1219 x 610) max. in 1" (25) increments. Type L is available in ceiling module sizes: 12" x 12", 24" x 12", 20" x 20", 24" x 24", 36" x 12", 36" x 24" and 48" x 24" (305 x 305, 610 x 305, 508 x 508, 610 x 610, 914 x 305, 914 x 610 and 1219 x 610). Fractional and metric sizes are available.
- 4. 1/2" x 1/2" x 1/2" (13 x 13 x 13) aluminum grid core is angled at 45° to prevent "see through" from three directions.
- 5. Sight resistant parallel to width/long dimension.
- Core is hinged and secured by 1/4 turn latches. Core panel is hinged on width dimension at top as standard (HT).

For other hinging requirements, specify one of the following:

- ☐ HB Hinged Bottom
- ☐ HL Hinged Left (facing grille)
- ☐ HR Hinged Right (facing grille)

- Type N standard fastening is with sheet metal screws, (by others), through the neck of the outer frame for Type S Surface Mount installation.
- 8. Standard Finish: AW Appliance White.

OPTIONS:

1. Finish:

SP Special ______.

- 2. Provision for 2" (51) filter (by others).
- 3. Core Fastening:
 - ☐ KK Knurled knob
 - QT 1/4 turn slotted fastener
- 4. Installation Fastening:
 - ☐ Type A Countersunk screwholes on face of outer frame (Type S Model).
- 5. Accessories:
 - ☐ GK Foam Gasket
 - EQT Earthquake Tabs

SCHEDULE TYPE:	Page 1 of 2			
PROJECT:	Dimensions are in inches (mm).			
ENGINEER:	DATE	B SERIES	SUPERSEDES	DRAWING NO.
CONTRACTOR:	9 - 24 - 19	51F	11 - 10 - 15	51FE45-1



ALUMINUM FILTER RETURN GRILLES

EGGCRATE GRID CORE 45° DEFLECTION • SIGHTPROOF

MODEL: 51FE45


Panel Mounted/Ceiling Modules


□ Border Type PLS: Steel Lay-in Panel□ Border Type PLA: Aluminum Lay-in Panel

The grille or register is mounted in an extended panel to suit standard T-Bar Lay-in type ceilings.

□ Border Type FPS: Steel Fineline® Panel□ Border Type FPA: Aluminum Fineline® Panel

The grille or register is mounted in an extended panel that will fit a 9/16" (14) narrow regressed (bolt slot) T-Bar ceiling grid or 9/16" (14) Flat T-Bar with tegular ceiling tile.





Available Border Type PL and FP Ceiling Module Sizes

Ceiling Module					
Imperial Units (in.)	Metric Units (mm)				
12 x 12	300 x 300				
24 x 12	600 x 300				
36 x 12	900 x 300				
48 x 12	1200 x 300				
20 x 20	500 x 500				
24 x 24	600 x 600				
36 x 24	900 x 600				
48 x 24	1200 x 600				

Maximum grille neck size is CM Ceiling Module - 6" (152).

SCHEDULE TYPE:	Page 2 of 2			
PROJECT:	Dimensions are in inches (mm).			
ENGINEER:	DATE	B SERIES	SUPERSEDES	DRAWING NO.
CONTRACTOR:	9 - 24 - 19	51F	11 - 10 - 15	51FE45-1