


STEEL HEAVY DUTY FILTER RETURN GRILLES FIXED LOUVERED BLADES • GYMNASIUM MODELS: 61FB45-HD AND 61FBS-HD



QUICK RELEASE FASTENERS

MODELS:

- **61FB45-HD** 45° deflection, 1/2" (13) spacing
- □ 61FBS-HD 0° deflection, 1/2" (13) spacing

FRAME/BORDER:


Type S Surface Mount

DESCRIPTION:

- 1. Material: Corrosion-resistant steel. Aluminum filter frame.
- 2. Grille Construction: Fixed blade angles in 45° or 0° deflection are 14 gauge material welded in position with support mullions on maximum 6" (152) centers. Frame is heavy duty 16 gauge material with welded and reinforced mitered corners.
- 3. Provision for 1" (25) filter (by others) is standard.
- 4. Type S available in nominal sizes 6" x 4" (152 x 102) through 36" x 24" (914 x 610) maximum with hinge. 48" x 36" (1219 x 914) maximum with QTO fasteners on all four sides.
- 5. Blades are parallel to width (first dimension).
- 6. Core is hinged and secured by 1/4 turn fasteners.
- 7. Hinge Orientation (blade deflection for 45 model shown by arrow).

Rectangular grilles: Parallel to long dimension on right hand side.

Square grilles: Parallel to width/blade orientation on top side.




W > H OR EQUAL:

د در ه بل ه ژه د (ه بل ه ژه در ه ب

A

FRONT VIEW



- 8. Type N standard fastening is with sheet metal screws, (by others), through the neck of the outer frame for Type S Surface Mount installation.
- 9. Standard Finish: AW Appliance White.

e

OPTIONS:

- 1. Finish:
 - SP Special
- Provision for 2" (51) filter (by others). 2. 🖵 F2
- 3. Core Fastening:
 - QTO 1/4 turn slotted fasteners only (no hinge).

SCHEDULE TYPE:	Dimensions are in inches (mm).			
PROJECT:				
ENGINEER:	DATE	B SERIES	SUPERSEDES	DRAWING NO.
CONTRACTOR:	8 - 27 - 21	61F	NEW	61F-HD