




**PATTERN CEILING DIFFUSERS**  
**ALUMINUM • SQUARE, RECTANGULAR OR**  
**ROUND NECK**  
**MODELS: 6200 AND 6200-O TYPE M**


**TYPE M METAL PAN (SNAP-IN)**



If the ceiling module is not 3" (76) larger than the neck size of the diffuser in both dimensions, a steel, module sized extended panel will be added.  
 Minimum duct size: 6 x 6 (152 x 152).  
 Maximum duct size: see table.  
 Available in 3" (76) increments only.

IMPERIAL MODULES		METRIC MODULES		METRIC MODULES	
Imperial Units (in.)	Metric Units (mm)	Imperial Units (in.)	Metric Units (mm)	Imperial Units (in.)	Metric Units (mm)
CM	Maximum Duct Size	CM	Maximum Duct Size	CM	Maximum Duct Size
12 x 12	9 x 9	305 x 305	229 x 229	300 x 300	152 x 152
24 x 12	21 x 9	610 x 305	533 x 229	600 x 300	457 x 152
24 x 24	21 x 21	610 x 610	533 x 533	600 x 600	457 x 457

**CORE STYLE SELECTION**



Patterns are shown in plan view (looking down into inlet).

**DESCRIPTION:**

1. Material: Aluminum. Extended panel where required is corrosion-resistant coated steel.
2. Model 6200 is a high capacity ceiling diffuser available in 1, 2, 3 or 4-way blow patterns to provide a tight horizontal airflow pattern from maximum to minimum airflow. Ideal for VAV applications.
3. Spring-loaded removable core.
4. Standard finish is AW Appliance White.

**OPTIONS:**

- PLA Aluminum Extended Panel.
- SQUARE AND RECTANGULAR NECK
- Steel opposed blade damper. Model 6200-O.
- Aluminum opposed blade damper. Model 6200-OA.
- ROUND NECK
- SR Square to round transition collar
- SR-O Square to round transition collar for use over O.B.D.
- 4275 Radial Opposed Blade Damper (round)
- 4250 Radial Sliding Blade Damper (round)
- 4675 Butterfly Damper (round)

**EXTERNAL INSULATION**

- EX External Foil-Back Insulation, installed -R-4.2.

**OPTIONAL FINISH:**

- SP Special. Specify \_\_\_\_\_ .

<b>SCHEDULE TYPE:</b>	Dimensions are in inches (mm).			
<b>PROJECT:</b>				
<b>ENGINEER:</b>	<b>DATE</b>	<b>B SERIES</b>	<b>SUPERSEDES</b>	<b>DRAWING NO.</b>
<b>CONTRACTOR:</b>	2 - 8 - 18	6200	11 - 24 - 16	6200-6