

ARCHITECTURAL CEILING DIFFUSER STEEL • ROUND NECK • PLAQUE FACE MODEL: 66UNI 24"x 24" CEILING MODULE

□ TYPE L Lay-in T-Bar





OF 2 SLOT	UNIT.	

Ceiling Module Size CM	No. of Slots	Nominal Round Duct Size D	Plaque Face P
	1	6,8,10 (152, 203, 254)	18 5/16 (465)
24 x 24	2	6,8,10,12 (152, 203, 254, 305)	15 5/16 (389)
(610 X 610)	3	8,10,12,14 (203, 254, 305, 356)	12 5/16 (313)



DESCRIPTION:

1. Material: Corrosion resistant steel

2. Model 66UNI is a flush face architecturally appealing plaque diffuser available with 1, 2 or 3 perimeter slots. The 66UNI provides a tight horizontal air pattern from maximum to minimum airflow and is ideal for VAV applications.

3. The 66UNI has been designed specifically to integrate with 24" x 24" (610 x 610) module ceiling suspension systems. Available in two frame/border styles. Type L Lay-in for standard 15/16" (24) or 9/16" (14) flat face T-bar systems. Type F Fineline® for Narrow Regressed T-Bar ceiling suspension systems, commonly refereed to as Bolt Slot or Fineline type T-Bar.

4. The 66UNI is provided with a deep plenum back pan to provide optimum performance by minimizing pressure drop and noise. The diffuser has a round neck collar for easy flexible duct connection.

5. Spring loaded removable core.

6. Standard finish is AW Appliance White.

Fineline® is a registered trademark of USG Interiors Inc.

OPTIONS:

- Special Finish. Specify: _____
- EQT. Earthquake Tabs.

ACCESSORIES:

- □ 4250 Radial sliding sliding blade dumper.
- □ 4275 Radial Opposed blade damper.

SCHEDULE TYPE	Dimonsions are in inches (mm)			
PROJECT				
ENGINEER	DATE	B SERIES	SUPERSEDES	DRAWING NO.
CONTRACTOR	2 - 26 - 02	6600	NEW	66UNI-1

Nailor Industries Inc. reserves the right to change any information concerning product or pricing without notice.