

## Performance Data

**Models 4360, 4360A, 4360AA • Flush Face • Return Module**  
**4365, 4365A, 4365AA • Drop Face • Return Module**

### Metric Units

| Ceiling Module | Neck Size   | Neck Velocity, M/S | 1.52 | 2.03 | 2.54 | 3.05 | 3.56 | 4.06 | 5.08 | 6.10 | 7.11  |
|----------------|-------------|--------------------|------|------|------|------|------|------|------|------|-------|
|                |             | Negative SP        | 6.0  | 10.4 | 16.7 | 23.9 | 32.3 | 42.3 | 66.1 | 95.2 | 129.8 |
|                | millimeters | VP                 | 1.4  | 2.5  | 3.9  | 5.6  | 7.6  | 9.9  | 15.5 | 22.3 | 30.4  |
| 300 x 300      | 152 dia.    | Airflow, L/S       | 28   | 37   | 46   | 56   | 65   | 74   | 92   | 111  | 130   |
|                |             | NC                 | —    | —    | —    | 10   | 14   | 18   | 27   | 32   | 38    |
|                | 152 x 152   | Airflow, L/S       | 35   | 47   | 59   | 71   | 83   | 94   | 118  | 142  | 165   |
|                |             | NC                 | —    | —    | —    | 12   | 17   | 21   | 30   | 35   | 41    |
|                | 203 dia.    | Airflow, L/S       | 50   | 66   | 83   | 99   | 115  | 132  | 165  | 198  | 231   |
|                |             | NC                 | —    | —    | 10   | 16   | 21   | 25   | 32   | 39   | 44    |
|                | 203 x 203   | Airflow, L/S       | 63   | 84   | 105  | 126  | 147  | 168  | 210  | 252  | 294   |
|                |             | NC                 | —    | —    | 11   | 17   | 22   | 26   | 33   | 40   | 45    |
| 500 x 500      | 254 x 254   | Airflow, L/S       | 98   | 131  | 164  | 197  | 229  | 262  | 327  | 393  | 459   |
|                |             | NC                 | —    | —    | 18   | 24   | 29   | 33   | 40   | 47   | 52    |
| 600 x 300      | 457 x 457   | Airflow, L/S       | 319  | 425  | 531  | 637  | 743  | 849  | 1062 | 1274 | 1486  |
|                |             | NC                 | —    | 17   | 24   | 30   | 35   | 39   | 46   | 53   | 58    |
|                | 152 x 152   | Airflow, L/S       | 35   | 47   | 59   | 71   | 83   | 94   | 118  | 142  | 165   |
|                |             | NC                 | —    | —    | —    | 13   | 18   | 22   | 29   | 36   | 41    |
|                | 203 dia.    | Airflow, L/S       | 50   | 66   | 83   | 99   | 115  | 132  | 165  | 198  | 231   |
|                |             | NC                 | —    | —    | —    | 15   | 20   | 24   | 31   | 38   | 43    |
|                | 203 x 203   | Airflow, L/S       | 63   | 84   | 105  | 126  | 147  | 168  | 210  | 252  | 294   |
|                |             | NC                 | —    | —    | 10   | 16   | 21   | 25   | 32   | 39   | 44    |
| 600 x 600      | 457 x 152   | Airflow, L/S       | 106  | 142  | 177  | 212  | 248  | 283  | 354  | 425  | 495   |
|                |             | NC                 | —    | —    | 14   | 20   | 25   | 28   | 35   | 42   | 47    |
|                | 559 x 254   | Airflow, L/S       | 216  | 288  | 361  | 433  | 504  | 577  | 721  | 865  | 1009  |
|                |             | NC                 | —    | 15   | 21   | 27   | 32   | 37   | 44   | 51   | 56    |
|                | 152 dia.    | Airflow, L/S       | 28   | 37   | 46   | 56   | 65   | 74   | 92   | 111  | 130   |
|                |             | NC                 | —    | —    | —    | 10   | 15   | 19   | 26   | 33   | 38    |
|                | 152 x 152   | Airflow, L/S       | 35   | 47   | 59   | 71   | 83   | 94   | 118  | 142  | 165   |
|                |             | NC                 | —    | —    | —    | 12   | 17   | 21   | 30   | 35   | 41    |
| 600 x 600      | 203 dia.    | Airflow, L/S       | 50   | 66   | 83   | 99   | 115  | 132  | 165  | 198  | 231   |
|                |             | NC                 | —    | —    | —    | 14   | 19   | 23   | 30   | 37   | 42    |
|                | 203 x 203   | Airflow, L/S       | 63   | 84   | 105  | 126  | 147  | 168  | 210  | 252  | 294   |
|                |             | NC                 | —    | —    | —    | 15   | 20   | 24   | 31   | 38   | 43    |
|                | 254 dia.    | Airflow, L/S       | 77   | 103  | 129  | 154  | 180  | 206  | 257  | 309  | 361   |
|                |             | NC                 | —    | —    | 10   | 16   | 21   | 25   | 32   | 39   | 44    |
|                | 254 x 254   | Airflow, L/S       | 98   | 131  | 164  | 197  | 229  | 262  | 327  | 393  | 459   |
|                |             | NC                 | —    | —    | 11   | 17   | 22   | 26   | 33   | 40   | 45    |
|                | 305 dia.    | Airflow, L/S       | 111  | 148  | 185  | 222  | 260  | 296  | 370  | 445  | 519   |
|                |             | NC                 | —    | —    | 13   | 19   | 24   | 28   | 35   | 42   | 47    |
|                | 305 x 305   | Airflow, L/S       | 142  | 189  | 236  | 283  | 330  | 378  | 472  | 566  | 661   |
|                |             | NC                 | —    | —    | 14   | 20   | 25   | 29   | 36   | 43   | 48    |
|                | 356 dia.    | Airflow, L/S       | 151  | 202  | 252  | 302  | 353  | 403  | 504  | 605  | 706   |
|                |             | NC                 | —    | —    | 15   | 21   | 26   | 30   | 37   | 44   | 49    |
|                | 356 x 356   | Airflow, L/S       | 193  | 257  | 321  | 386  | 450  | 514  | 642  | 771  | 899   |
|                |             | NC                 | —    | 10   | 17   | 23   | 28   | 32   | 39   | 46   | 51    |
|                | 381 x 381   | Airflow, L/S       | 221  | 295  | 369  | 443  | 516  | 590  | 738  | 885  | 1033  |
|                |             | NC                 | —    | 12   | 19   | 25   | 30   | 34   | 41   | 48   | 53    |
|                | 406 dia.    | Airflow, L/S       | 198  | 264  | 329  | 395  | 461  | 527  | 659  | 791  | 923   |
|                |             | NC                 | —    | 10   | 17   | 23   | 28   | 32   | 39   | 46   | 51    |
| 1200 x 600     | 457 dia.    | Airflow, L/S       | 250  | 334  | 417  | 500  | 584  | 667  | 834  | 1001 | 1167  |
|                |             | NC                 | —    | 12   | 19   | 25   | 30   | 32   | 41   | 48   | 53    |
|                | 457 x 457   | Airflow, L/S       | 319  | 425  | 531  | 637  | 743  | 849  | 1062 | 1274 | 1486  |
|                |             | NC                 | —    | 16   | 23   | 29   | 34   | 38   | 45   | 52   | 57    |
|                | 559 x 559   | Airflow, L/S       | 476  | 634  | 793  | 952  | 1110 | 1269 | 1586 | 1903 | 2221  |
|                |             | NC                 | —    | 18   | 25   | 31   | 36   | 40   | 47   | 51   | 59    |
|                | 1168 x 559  | Airflow, L/S       | 995  | 1327 | 1658 | 1990 | 2321 | 2653 | 3317 | 3980 | 4643  |
|                |             | NC                 | 11   | 20   | 27   | 34   | 38   | 43   | 50   | 57   | 62    |

**L/S** - liters per second  
**M/S** - meters per second velocity  
**VP** - velocity pressure - Pascals  
**SP** - static pressure - Pascals

**NC** - Noise Criteria (values) based on 10 dB room absorption, re 10<sup>-12</sup> watts.

### Performance Notes:

1. Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70 – 2023.