

PERFORMANCE DATA:

Models 4360, 4360A, 4360AA • Flush Face • Return Module
4365, 4365A, 4365AA • Drop Face • Return Module

Ceiling Module	Neck Size	Neck Velocity, FPM	300	400	500	600	700	800	1000	1200	1400
		Negative Static Pressure	.024	.042	.067	.096	.130	.170	.266	.383	.522
		Velocity Pressure	.006	.010	.016	.022	.031	.040	.062	.090	.122
		Airflow, CFM	59	78	98	118	137	157	196	236	275
12 x 12	6" Dia.	Noise Criteria	—	—	—	10	14	18	27	32	38
		Airflow, CFM	75	100	125	150	175	200	250	300	350
	8" Dia.	Noise Criteria	—	—	—	12	17	21	30	35	41
		Airflow, CFM	105	140	175	209	244	279	349	419	489
	8 x 8	Noise Criteria	—	—	10	16	21	25	32	39	44
		Airflow, CFM	133	178	222	267	311	356	444	533	622
	10 x 10	Noise Criteria	—	—	11	17	22	26	33	40	45
		Airflow, CFM	208	278	347	416	486	556	694	833	972
		Noise Criteria	—	—	18	24	29	33	40	47	52
		Airflow, CFM	675	900	1125	1350	1575	1800	2250	2700	3150
	18 x 18	Noise Criteria	—	17	24	30	35	39	46	53	58
		Airflow, CFM	75	100	125	150	175	200	250	300	350
24 x 12	6" Dia.	Noise Criteria	—	—	—	13	18	22	29	36	41
		Airflow, CFM	105	140	175	209	244	279	349	419	489
	8" Dia.	Noise Criteria	—	—	—	15	20	24	31	38	43
		Airflow, CFM	133	178	222	267	311	356	444	533	622
	8 x 8	Noise Criteria	—	—	10	16	21	25	32	39	44
		Airflow, CFM	225	300	375	450	525	600	750	900	1050
	18 x 6	Noise Criteria	—	—	14	20	25	28	35	42	47
		Airflow, CFM	458	611	764	917	1069	1222	1528	1833	2139
	22 x 10	Noise Criteria	—	15	21	27	34	37	44	51	56
		Airflow, CFM	59	79	98	118	137	157	196	236	275
	6" Dia.	Noise Criteria	—	—	—	10	15	19	26	33	38
		Airflow, CFM	75	100	125	150	175	200	250	300	350
24 x 24	6 x 6	Noise Criteria	—	—	—	12	17	21	28	35	41
		Airflow, CFM	105	140	175	209	244	279	349	419	489
	8" Dia.	Noise Criteria	—	—	—	14	19	23	30	37	42
		Airflow, CFM	133	178	222	267	311	356	444	533	622
	8 x 8	Noise Criteria	—	—	—	15	20	24	31	38	43
		Airflow, CFM	164	218	273	327	382	436	545	655	764
	10" Dia.	Noise Criteria	—	—	10	16	21	25	32	39	44
		Airflow, CFM	208	278	347	417	486	556	694	833	972
	10 x 10	Noise Criteria	—	—	11	17	22	26	33	40	45
		Airflow, CFM	236	314	393	471	550	628	785	942	1100
	12" Dia.	Noise Criteria	—	—	13	19	24	28	35	42	47
		Airflow, CFM	300	400	500	600	700	800	1000	1200	1400
	12 x 12	Noise Criteria	—	—	14	20	25	29	36	43	48
		Airflow, CFM	321	428	535	641	748	855	1069	1283	1497
	14" Dia.	Noise Criteria	—	—	15	21	26	30	37	44	49
		Airflow, CFM	408	544	681	817	953	1089	1361	1633	1906
	14 x 14	Noise Criteria	—	10	17	23	28	32	39	46	51
		Airflow, CFM	469	625	781	938	1094	1250	1563	1875	2188
	15 x 15	Noise Criteria	—	12	19	25	30	34	41	48	53
		Airflow, CFM	419	559	698	838	977	1117	1396	1676	1955
	16" Dia.	Noise Criteria	—	10	17	23	28	32	39	46	51
		Airflow, CFM	530	707	884	1060	1237	1414	1767	2121	2474
	18" Dia.	Noise Criteria	—	12	19	25	30	32	39	46	51
		Airflow, CFM	675	900	1125	1350	1575	1800	2250	2700	3150
	18 x 18	Noise Criteria	—	16	23	29	34	38	45	52	57
		Airflow, CFM	1008	1344	1681	2017	2353	2689	3361	4033	4706
	22 x 22	Noise Criteria	—	18	25	31	36	40	47	51	59
		Airflow, CFM	2108	2811	3514	4217	4919	5622	7028	8433	9839
48 x 24	46 x 22	Noise Criteria	11	20	27	34	38	43	50	57	62

Performance Notes:

- All pressures are in inches w.g..
- Noise Criteria (NC) values are based

upon 10 dB room absorption, re 10⁻¹² watts. Dash (—) in space indicates an Noise Criteria of less than 10.

3. Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70 – 2023.