

PERFORMANCE DATA:

Models 4320F, 4320FA, 4320FAA, 4325F, 4325FA, 4325FAA • 24 x 24 (600 x 600) Module Size • Round Neck

Nominal Neck Size	Neck Velocity, FPM		300	400	500	600	700	800	900
	Velocity Pressure		.006	.010	.016	.023	.031	.040	.051
	Total Pressure		.026	.047	.073	.105	.143	.186	.236
6" Dia.	Flow Rate, CFM		60	80	95	115	135	155	175
	Throw	4-Way	1-2-4	2-3-6	2-3-7	3-4-7	3-5-8	4-6-9	4-6-9
		3-Way	1-2-5	2-3-7	2-4-8	3-5-9	4-6-9	4-7-10	5-7-11
		2-Way	2-3-7	3-4-9	4-6-11	4-7-12	5-8-13	6-9-14	7-11-15
		1-Way	2-4-8	3-5-11	4-7-13	5-8-15	6-9-16	7-11-17	8-12-18
	Noise Criteria		—	—	17	23	28	33	36
8" Dia.	Flow Rate, CFM		105	140	175	210	245	280	315
	Throw	4-Way	2-3-6	2-4-8	3-5-9	4-6-10	4-7-11	4-8-12	5-9-12
		3-Way	2-3-7	3-4-9	3-5-11	4-7-12	5-8-13	6-9-14	7-10-14
		2-Way	3-4-9	4-6-13	5-8-15	6-9-17	7-11-18	8-13-20	9-14-21
		1-Way	3-5-11	5-7-15	6-9-18	7-11-21	8-13-22	10-15-24	11-17-25
	Noise Criteria		—	—	20	26	31	36	39
10" Dia.	Flow Rate, CFM		165	215	270	325	380	435	490
	Throw	4-Way	2-3-7	3-5-10	4-6-12	5-7-13	5-8-14	6-10-15	7-11-16
		3-Way	2-4-8	3-5-11	4-7-13	5-8-15	6-10-16	7-11-17	8-13-18
		2-Way	4-6-12	5-8-16	6-10-20	8-12-22	9-14-23	10-16-25	12-18-27
		1-Way	4-7-14	6-9-18	7-11-23	9-14-26	11-16-28	12-18-29	14-22-31
	Noise Criteria		—	15	23	29	34	38	40
12" Dia.	Flow Rate, CFM		235	315	390	470	550	625	705
	Throw	4-Way	3-4-9	4-6-12	5-7-14	6-9-15	7-10-17	8-12-18	9-13-20
		3-Way	3-5-10	4-7-14	5-8-16	7-10-18	8-12-20	9-14-22	10-15-23
		2-Way	4-7-14	6-9-20	8-12-24	9-14-26	11-17-28	13-20-30	14-23-32
		1-Way	5-8-17	7-11-23	9-14-28	11-17-31	13-20-33	15-23-35	17-26-37
	Noise Criteria		—	16	24	30	35	39	41
14" Dia.	Flow Rate, CFM		320	425	535	640	750	855	960
	Throw	4-Way	3-5-10	4-7-14	5-8-16	7-10-18	8-12-21	9-14-22	10-16-23
		3-Way	4-6-12	5-8-16	6-10-20	8-12-22	9-14-24	10-16-25	12-18-27
		2-Way	5-8-17	7-11-24	9-14-28	11-17-30	13-21-33	15-24-35	17-26-37
		1-Way	6-9-20	8-13-27	11-16-33	13-20-36	15-24-38	17-27-41	20-30-43
	Noise Criteria		—	18	26	32	37	41	43
15" Dia.	Flow Rate, CFM		370	490	615	740	860	985	1100
	Throw	4-Way	3-6-10	4-2-14	5-8-17	8-10-19	8-13-21	10-14-23	10-16-24
		3-Way	4-6-12	6-8-17	6-11-21	8-13-22	10-14-25	11-16-26	13-18-28
		2-Way	4-8-17	7-12-25	9-15-30	11-18-31	13-22-34	16-25-35	17-27-38
		1-Way	6-9-20	8-14-28	12-17-34	14-21-37	16-24-39	18-27-42	17-31-43
	Noise Criteria		—	19	27	33	38	42	44
16" Dia.	Flow Rate, CFM		420	560	700	835	975	1115	1255
	Throw	4-Way	4-6-12	5-8-16	6-10-20	8-12-22	9-14-23	10-16-25	12-18-26
		3-Way	4-7-14	6-9-18	7-11-23	9-14-25	10-16-27	12-18-29	14-22-30
		2-Way	6-9-20	8-13-27	10-16-32	13-20-35	15-24-37	17-27-40	20-30-42
		1-Way	7-11-23	10-15-31	12-18-37	15-23-41	17-27-44	21-31-47	23-35-50
	Noise Criteria		—	21	28	34	39	43	45

For performance notes, see page D185.

PERFORMANCE DATA:

Models 4320F, 4320FA, 4320FAA, 4325F, 4325FA, 4325FAA • 24 x 24 (600 x 600) Module Size • Square Neck

Nominal Neck Size	Neck Velocity, FPM		300	400	500	600	700	800	900
	Velocity Pressure		.006	.010	.016	.023	.031	.040	.051
	Total Pressure		.025	.045	.070	.100	.137	.179	.226
6 x 6	Flow Rate, CFM		75	100	125	150	175	200	225
	Throw	4-Way	1-2-5	2-3-7	3-4-8	3-5-8	4-6-9	5-7-10	5-7-11
		3-Way	2-3-6	2-4-8	3-5-11	4-6-12	5-7-13	5-8-14	6-10-15
		2-Way	3-4-9	4-6-12	5-7-15	6-9-17	7-10-20	8-12-21	9-14-22
		1-Way	3-5-10	4-7-14	6-9-18	7-10-21	8-12-23	9-14-24	10-16-26
Noise Criteria		—	—	18	24	29	34	37	
8 x 8	Flow Rate, CFM		135	175	220	265	310	355	400
	Throw	4-Way	2-3-6	3-4-9	3-5-10	4-6-11	5-8-12	6-9-13	6-10-14
		3-Way	2-3-7	3-5-10	4-6-12	5-7-13	6-9-14	7-10-15	7-11-16
		2-Way	3-5-11	4-7-14	6-9-17	7-11-20	8-13-21	9-14-23	11-16-24
		1-Way	4-6-12	5-8-17	7-10-21	8-12-23	9-14-25	11-17-27	12-20-28
Noise Criteria		—	—	21	27	32	37	40	
10 x 10	Flow Rate, CFM		210	275	345	415	485	555	625
	Throw	4-Way	2-4-8	3-5-11	4-7-13	5-8-14	6-10-16	7-11-17	8-12-18
		3-Way	3-4-9	4-6-13	5-8-15	6-9-17	7-11-18	8-13-20	9-14-22
		2-Way	4-6-13	6-9-18	7-11-22	9-13-25	10-16-26	12-18-28	13-21-30
		1-Way	5-8-16	7-10-22	8-13-26	10-16-29	12-18-31	14-22-33	16-25-35
Noise Criteria		—	16	24	30	35	39	41	
12 x 12	Flow Rate, CFM		300	400	500	600	700	800	900
	Throw	4-Way	3-5-10	4-6-13	5-8-16	6-10-17	8-12-20	9-13-21	10-15-22
		3-Way	3-5-11	5-7-15	6-9-18	7-11-21	9-13-23	10-15-24	11-17-26
		2-Way	5-8-16	7-11-23	9-13-27	11-16-29	13-20-32	14-23-34	16-25-36
		1-Way	6-9-20	8-12-26	10-16-31	12-20-34	14-23-37	17-26-40	22-31-44
Noise Criteria		—	17	25	31	36	40	42	
14 x 14	Flow Rate, CFM		410	545	680	815	955	1090	1360
	Throw	4-Way	1-1-6	1-3-8	2-4-11	3-6-13	4-7-15	5-8-17	7-11-22
		3-Way	1-3-10	2-6-14	4-9-18	6-10-21	8-12-26	9-14-29	11-18-372
		2-Way	2-5-14	4-9-19	7-12-24	9-14-30	11-17-35	13-19-40	16-24-47
		1-Way	3-8-17	6-11-23	9-14-30	11-17-1936	13-20-42	15-23-48	19-30-54
Noise Criteria		—	19	27	33	38	42	44	
15 x 15	Flow Rate, CFM		470	625	780	935	1095	1250	1405
	Throw	4-Way	4-6-12	5-8-17	7-10-21	8-12-23	10-15-25	11-17-26	12-20-28
		3-Way	4-7-14	6-9-20	8-12-24	9-14-26	11-17-28	13-20-30	14-23-32
		2-Way	6-10-21	9-13-28	11-17-33	13-21-37	16-25-40	18-28-42	21-32-45
		1-Way	8-12-25	10-16-33	13-21-39	16-25-43	18-29-46	22-33-49	25-37-53
Noise Criteria		—	20	28	33	39	43	45	
16 x 16	Flow Rate, CFM		530	710	890	1065	1245	1420	1600
	Throw	4-Way	4-7-14	5-9-18	7-10-20	9-13-24	10-16-26	10-19-28	13-21-29
		3-Way	4-7-17	6-10-21	8-12-24	10-15-28	11-20-30	13-22-32	17-24-34
		2-Way	7-10-23	10-14-29	11-17-34	15-22-36	18-28-43	20-30-44	24-34-50
		1-Way	8-12-26	11-17-33	14-21-40	18-25-45	21-32-50	23-38-53	29-40-56
Noise Criteria		—	22	29	35	40	44	45	

Performance Notes:

1. All pressures are in inches w.g..
2. Throws are given at 150, 100 and 50 fpm terminal velocities under isothermal conditions.
3. Noise Criteria (NC) values are based upon 10 dB room absorption, re 10⁻¹² watts. Dash (—) in space indicates an Noise Criteria of less than 15.

4. Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70 – 2023.

Balancing:

It is recommended that a commercially available 'Flow Hood' is used for field balancing. The airflow meter directly reads average flow rate with great accuracy at all volumes. It is a much faster and more accurate alternative to time consuming multiple velocity readings, eliminating the use of Ak factors and the calculations required to convert the average velocity into airflow.