

PERFORMANCE DATA:

Models 5075RCTD, 5075RCTD-F • 3/4" (19) Slot • Return

No. of Slots	Negative Static Pressure	.006	.028	.065	.110	.170	.250	.350	.465
1	CFM	70	140	210	280	350	420	490	560
	Noise Criteria	—	—	16	24	30	35	39	43
2	CFM	130	260	390	520	650	780	910	1040
	Noise Criteria	—	—	19	27	33	38	42	46
3	CFM	180	360	540	720	900	1080	1260	1440
	Noise Criteria	—	10	21	29	35	40	44	48
4	CFM	220	440	660	880	1100	1320	1540	1760
	Noise Criteria	—	10	21	29	35	40	44	48

Models 5010RCTD, 5010RCTD-F • 1" (25) Slot • Return

No. of Slots	Negative Static Pressure	.006	.028	.065	.110	.170	.250	.350	.465
1	CFM	140	210	280	350	420	490	560	700
	Noise Criteria	—	—	17	23	28	32	36	42
2	CFM	253	380	507	633	760	887	1013	1267
	Noise Criteria	—	12	20	26	31	35	39	45
3	CFM	340	510	680	850	1020	1190	1360	1700
	Noise Criteria	—	13	21	27	32	36	40	46
4	CFM	400	600	800	1000	1200	1400	1600	2000
	Noise Criteria	—	14	22	28	33	37	41	47

Performance Notes:

1. All pressures are in inches w.g..

2. Noise Criteria (NC) values are based upon 10dB room absorption, re 10⁻¹² watts. Dash (—) in space indicates an Noise Criteria of less than 10.

3. Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70 – 2023.