

PERFORMANCE DATA:

MODEL 5375(I) • 3/4" (19) SLOT WIDTH

1 Slot • 24" (610) Long

6" Round Inlet	Airflow, CFM	20	30	40	50	60	70	80	90
	Total Pressure	.014	.031	.055	.085	.123	.168	.219	.277
	Noise Criteria	–	–	20	26	30	34	37	40
	Throw	2-4-08	4-6-11	6-8-13	7-10-14	8-11-16	9-12-17	9-12-18	10-13-18
8" Round Inlet	Airflow, CFM	30	40	50	60	70	80	90	100
	Total Pressure	.026	.046	.073	.104	.142	.186	.235	.290
	Noise Criteria	–	17	22	26	30	32	35	38
	Throw	4-6-11	6-8-13	7-10-14	8-11-16	9-12-17	9-12-18	10-13-18	11-14-19
10" Oval Inlet	Airflow, CFM	40	50	60	70	80	90	100	110
	Total Pressure	.037	.058	.084	.114	.149	.188	.232	.281
	Noise Criteria	–	18	22	26	29	32	35	37
	Throw	6-8-13	7-10-14	8-11-16	9-12-17	9-12-18	10-13-18	11-14-19	11-14-20

1 Slot • 48" (1219) Long

6" Round Inlet	Airflow, CFM	35	50	65	80	95	110	125	140
	Total Pressure	.012	.024	.040	.061	.086	.115	.149	.187
	Noise Criteria	–	17	22	27	30	33	36	39
	Throw	2-5-11	5-8-14	7-10-17	8-12-19	10-13-20	11-14-22	12-16-23	13-17-24
8" Round Inlet	Airflow, CFM	50	65	80	95	110	125	140	155
	Total Pressure	.020	.034	.052	.073	.098	.127	.159	.195
	Noise Criteria	–	17	22	26	29	31	34	37
	Throw	5-8-14	7-10-17	8-12-19	10-13-20	11-14-22	12-16-23	13-17-24	13-17-25
10" Oval Inlet	Airflow, CFM	65	80	95	110	125	140	155	170
	Total Pressure	.027	.042	.059	.079	.101	.127	.156	.188
	Noise Criteria	–	19	23	27	30	32	34	37
	Throw	7-10-17	8-12-19	10-13-20	11-14-22	12-16-23	13-17-24	13-17-25	14-18-26
12" Oval Inlet	Airflow, CFM	80	95	110	125	140	155	170	185
	Total Pressure	.037	.052	.070	.090	.113	.138	.166	.197
	Noise Criteria	16	20	23	26	29	31	34	36
	Throw	8-12-19	10-13-20	11-14-22	12-16-23	13-17-24	13-17-25	14-18-26	15-19-26

1 Slot • 60" (1524) Long

8" Round Inlet	Airflow, CFM	80	95	110	125	140	155	170	185
	Total Pressure	.039	.055	.074	.095	.119	.146	.176	.209
	Noise Criteria	18	22	26	29	32	35	36	39
	Throw	8-11-18	9-13-20	10-14-22	11-15-23	12-16-24	13-17-25	14-18-26	15-19-27
10" Oval Inlet	Airflow, CFM	95	110	125	140	155	170	185	200
	Total Pressure	.050	.068	.087	.110	.134	.162	.191	.224
	Noise Criteria	20	23	26	29	31	33	35	37
	Throw	9-13-20	10-14-22	11-15-23	12-16-24	13-17-25	14-18-26	15-19-27	15-20-28
12" Oval Inlet	Airflow, CFM	110	125	140	155	170	185	200	215
	Total Pressure	.048	.062	.078	.095	.115	.136	.159	.184
	Noise Criteria	21	24	26	29	31	33	36	37
	Throw	10-14-22	11-15-23	12-16-24	13-17-25	14-18-26	15-19-27	15-20-28	16-21-29

Performance Notes:

1. Throws are given at 150, 100 and 50 fpm terminal velocities under isothermal conditions.
2. Total Pressure is in inches w.g..
3. Noise Criteria [NC] values based on 10 dB room absorption, re 10⁻¹² watts.
4. Cataloged throws are for a one-way horizontal air pattern. For divided airflow, deduce the airflow in each direction according to the number of slots, with the total airflow apportioned

between the slots. Look up throw for the airflow in each direction according to the number of slots in that direction.

5. Performance data is based upon the standard **5300 Series** Model. The **5300MP** Modified Performance Series reduces the tabulated throw values by approximately 25%. Horizontal spread values are approximately 150% of the horizontal throw (T) projection values.

6. Dash (–) in space indicates an Noise Criteria level of less than 15.

7. Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70–2023.

Number of Slots	Ak Factor per foot	
	Supply	Return
1	.024	.039
2	.049	.078
3	.073	.117
4	.098	.156

PERFORMANCE DATA:

MODEL 5375(I) • 3/4" (19) SLOT WIDTH

2 Slot • 24" (610) Long

6" Round Inlet	Airflow, CFM	50	65	80	95	110	125	140	155
	Total Pressure	.027	.045	.068	.096	.129	.167	.209	.257
	Noise Criteria	16	21	26	30	34	37	40	43
	Throw	5-8-15	7-10-18	9-12-20	10-14-22	11-15-23	12-16-25	13-17-26	13-17-27
8" Round Inlet	Airflow, CFM	65	80	95	110	125	140	155	170
	Total Pressure	.036	.055	.077	.103	.134	.168	.205	.247
	Noise Criteria	17	22	26	29	32	35	38	41
	Throw	7-10-18	9-12-20	10-14-22	11-15-23	12-16-25	13-17-26	13-17-27	14-18-28
10" Oval Inlet	Airflow, CFM	80	95	110	125	140	155	170	185
	Total Pressure	.044	.062	.083	.107	.134	.164	.197	.234
	Noise Criteria	16	22	26	30	33	36	39	41
	Throw	9-12-20	10-14-22	11-15-23	12-16-25	13-17-26	13-17-27	14-18-28	15-19-29

2 Slot • 48" (1219) Long

6" Round Inlet	Airflow, CFM	60	80	100	120	140	160	180	200
	Total Pressure	.022	.039	.061	.088	.119	.156	.198	.244
	Noise Criteria	–	16	21	25	29	32	35	38
	Throw	2-6-14	5-9-18	8-12-22	9-14-24	11-16-27	12-17-29	14-19-30	15-20-32
8" Round Inlet	Airflow, CFM	80	100	120	140	160	180	200	220
	Total Pressure	.022	.034	.049	.067	.088	.111	.137	.166
	Noise Criteria	–	15	19	23	27	30	33	36
	Throw	5-9-18	8-12-22	9-14-24	11-16-27	12-17-29	14-19-30	15-20-32	16-21-33
10" Oval Inlet	Airflow, CFM	100	120	140	160	180	200	220	240
	Total Pressure	.025	.036	.049	.064	.082	.101	.122	.145
	Noise Criteria	–	17	21	24	27	30	33	35
	Throw	8-12-22	9-14-24	11-16-27	12-17-29	14-19-30	15-20-32	16-21-33	17-22-35
12" Oval Inlet	Airflow, CFM	120	140	160	180	200	220	240	260
	Total Pressure	.031	.042	.055	.070	.086	.104	.124	.145
	Noise Criteria	–	15	18	23	26	29	32	34
	Throw	9-14-24	11-16-27	12-17-29	14-19-30	15-20-32	16-21-33	17-22-35	17-23-36

2 Slot • 60" (1524) Long

8" Round Inlet	Airflow, CFM	140	160	180	200	220	240	260	280
	Total Pressure	.054	.070	.089	.110	.133	.158	.186	.216
	Noise Criteria	20	23	26	28	31	33	35	37
	Throw	10-15-26	11-17-28	13-18-30	14-19-32	15-21-34	16-22-35	17-23-36	18-24-38
10" Oval Inlet	Airflow, CFM	160	180	200	220	240	260	280	300
	Total Pressure	.049	.063	.077	.093	.111	.130	.151	.174
	Noise Criteria	20	23	25	28	30	32	34	36
	Throw	11-17-28	13-18-30	14-19-32	15-21-34	16-22-35	17-23-36	18-24-38	19-25-39
12" Oval Inlet	Airflow, CFM	180	200	220	240	260	280	300	320
	Total Pressure	.044	.055	.066	.079	.092	.107	.123	.140
	Noise Criteria	20	23	25	27	29	31	33	35
	Throw	13-18-30	14-19-32	15-21-34	16-22-35	17-23-36	18-24-38	19-25-39	19-25-40

Performance Notes:

- Throws are given at 150, 100 and 50 fpm terminal velocities under isothermal conditions.
- Total Pressure is in inches w.g..
- Noise Criteria [NC] values based on 10 dB room absorption, re 10⁻¹² watts.
- Cataloged throws are for a one-way horizontal air pattern. For divided airflow, deduce the airflow in each direction according to the number of slots, with the total airflow apportioned

between the slots. Look up throw for the airflow in each direction according to the number of slots in that direction.

- Performance data is based upon the standard **5300 Series** Model. The **5300MP** Modified Performance Series reduces the tabulated throw values by approximately 25%. Horizontal spread values are approximately 150% of the horizontal throw (T) projection values.
- Dash (–) in space indicates an Noise Criteria level of less than 15.

- Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70–2023.

Number of Slots	Ak Factor per foot	
	Supply	Return
1	.024	.039
2	.049	.078
3	.073	.117
4	.098	.156

PERFORMANCE DATA:

MODEL 5375(I) • 3/4" (19) SLOT WIDTH

3 Slot • 24" (610) Long

6" Round Inlet	Airflow, CFM	60	80	100	120	140	160	180	200
	Total Pressure	.026	.047	.073	.106	.144	.188	.238	.294
	Noise Criteria	–	20	26	30	34	37	40	43
	Throw	5-8-16	8-11-20	10-13-23	11-15-25	12-17-27	14-18-29	15-19-31	15-20-32
8" Round Inlet	Airflow, CFM	80	100	120	140	160	180	200	220
	Total Pressure	.030	.047	.068	.093	.122	.154	.190	.230
	Noise Criteria	15	20	25	29	32	35	37	39
	Throw	8-11-20	10-13-23	11-15-25	12-17-27	14-18-29	15-19-31	15-20-32	16-21-33
10" Oval Inlet	Airflow, CFM	100	120	140	160	180	200	220	240
	Total Pressure	.040	.058	.078	.102	.130	.160	.194	.230
	Noise Criteria	19	23	27	30	33	35	37	39
	Throw	10-13-23	11-15-25	12-17-27	14-18-29	15-19-31	15-20-32	16-21-33	17-22-35

3 Slot • 48" (1219) Long

6" Round Inlet	Airflow, CFM	125	150	175	200	225	250	275	300
	Total Pressure	.074	.107	.145	.190	.240	.297	.359	.427
	Noise Criteria	20	24	28	32	35	37	39	41
	Throw	8-13-23	10-15-27	12-17-30	14-19-32	15-21-35	16-22-37	18-23-39	19-25-40
8" Round Inlet	Airflow, CFM	150	175	200	225	250	275	300	325
	Total Pressure	.057	.077	.101	.128	.157	.191	.227	.266
	Noise Criteria	20	24	27	30	33	35	37	39
	Throw	10-15-27	12-17-30	14-19-32	15-21-35	16-22-37	18-23-39	19-25-40	20-26-42
10" Oval Inlet	Airflow, CFM	175	200	225	250	275	300	325	350
	Total Pressure	.051	.067	.085	.104	.126	.150	.176	.204
	Noise Criteria	22	25	27	30	32	34	36	38
	Throw	12-17-30	14-19-32	15-21-35	16-22-37	18-23-39	19-25-40	20-26-42	20-27-43
12" Oval Inlet	Airflow, CFM	200	225	250	275	300	325	350	375
	Total Pressure	.041	.052	.064	.077	.092	.108	.125	.143
	Noise Criteria	20	23	26	28	30	32	34	38
	Throw	14-19-32	15-21-35	16-22-37	18-23-39	19-25-40	20-26-42	20-27-43	21-28-45

3 Slot • 60" (1524) Long

8" Round Inlet	Airflow, CFM	180	210	240	270	300	330	360	390
	Total Pressure	.069	.094	.123	.156	.192	.233	.277	.325
	Noise Criteria	21	25	28	31	34	36	38	40
	Throw	11-16-29	13-19-33	15-21-36	16-22-38	18-24-40	19-26-42	20-27-44	21-28-46
10" Oval Inlet	Airflow, CFM	210	240	270	300	330	360	390	420
	Total Pressure	.064	.084	.106	.131	.159	.189	.222	.257
	Noise Criteria	23	26	28	31	33	35	37	39
	Throw	13-19-33	15-21-36	16-22-38	18-24-40	19-26-42	20-27-44	21-28-46	22-29-48
12" Oval Inlet	Airflow, CFM	240	270	300	330	360	390	420	450
	Total Pressure	.049	.063	.077	.093	.111	.130	.151	.174
	Noise Criteria	22	24	27	29	31	33	35	37
	Throw	15-21-36	16-22-38	18-24-40	19-26-42	20-27-44	21-28-46	22-29-48	23-30-49

Performance Notes:

1. Throws are given at 150, 100 and 50 fpm terminal velocities under isothermal conditions.
2. Total Pressure is in inches w.g..
3. Noise Criteria [NC] values based on 10 dB room absorption, re 10⁻¹² watts.
4. Cataloged throws are for a one-way horizontal air pattern. For divided airflow, deduce the airflow in each direction according to the number of slots, with the total airflow apportioned

between the slots. Look up throw for the airflow in each direction according to the number of slots in that direction.

5. Performance data is based upon the standard **5300 Series** Model. The **5300MP** Modified Performance Series reduces the tabulated throw values by approximately 25%. Horizontal spread values are approximately 150% of the horizontal throw (T) projection values.
6. Dash (–) in space indicates an Noise Criteria level of less than 15.

7. Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70–2023.

Number of Slots	Ak Factor per foot	
	Supply	Return
1	.024	.039
2	.049	.078
3	.073	.117
4	.098	.156

PERFORMANCE DATA:

MODEL 5375(I) • 3/4" (19) SLOT WIDTH

4 Slot • 24" (610) Long

6" Round Inlet	Airflow, CFM	75	100	125	150	175	200	225	250
	Total Pressure	.033	.058	.091	.131	.179	.233	.295	.365
	Noise Criteria	16	21	27	31	35	38	41	44
	Throw	6-9-18	9-13-22	11-16-26	13-18-29	14-20-31	15-22-33	17-23-35	18-24-37
8" Round Inlet	Airflow, CFM	100	125	150	175	200	225	250	275
	Total Pressure	.031	.049	.070	.095	.124	.157	.194	.235
	Noise Criteria	17	22	26	31	34	37	39	41
	Throw	9-13-22	11-16-26	13-18-29	14-20-31	15-22-33	17-23-35	18-24-37	19-25-38
10" Oval Inlet	Airflow, CFM	125	150	175	200	225	250	275	300
	Total Pressure	.042	.060	.082	.107	.135	.167	.202	.240
	Noise Criteria	21	24	27	31	34	36	38	40
	Throw	11-16-26	13-18-29	14-20-31	15-22-33	17-23-35	18-24-37	19-25-38	19-27-39

4 Slot • 48" (1219) Long

6" Round Inlet	Airflow, CFM	160	190	220	250	280	310	340	370
	Total Pressure	.074	.159	.213	.275	.345	.422	.508	.602
	Noise Criteria	23	27	30	33	35	38	40	42
	Throw	9-14-27	12-18-31	14-20-34	16-22-37	17-24-39	19-26-42	20-28-44	21-29-46
8" Round Inlet	Airflow, CFM	190	220	250	280	310	340	370	400
	Total Pressure	.071	.096	.124	.155	.190	.229	.271	.317
	Noise Criteria	22	25	28	31	33	36	38	40
	Throw	12-18-31	14-20-34	16-22-37	17-24-39	19-26-42	20-28-44	21-29-46	22-31-47
10" Oval Inlet	Airflow, CFM	220	250	280	310	340	370	400	430
	Total Pressure	.064	.082	.103	.126	.152	.180	.210	.243
	Noise Criteria	22	25	28	31	33	35	37	39
	Throw	14-20-34	16-22-37	17-24-39	19-26-42	20-28-44	21-29-46	22-31-47	23-32-49
12" Oval Inlet	Airflow, CFM	250	280	310	340	370	400	430	460
	Total Pressure	.046	.057	.070	.084	.100	.117	.135	.155
	Noise Criteria	21	24	27	29	31	33	35	37
	Throw	16-22-37	17-24-39	19-26-42	20-28-44	21-29-46	22-31-47	23-32-49	24-33-50

4 Slot • 60" (1524) Long

8" Round Inlet	Airflow, CFM	220	260	300	340	380	420	460	500
	Total Pressure	.089	.124	.165	.212	.265	.324	.389	.459
	Noise Criteria	22	26	29	32	35	37	39	41
	Throw	12-18-33	15-21-37	17-24-40	19-27-43	20-29-46	22-31-49	23-33-51	25-34-53
10" Oval Inlet	Airflow, CFM	260	300	340	380	420	460	500	540
	Total Pressure	.077	.103	.132	.165	.201	.242	.285	.333
	Noise Criteria	23	26	29	32	35	37	39	41
	Throw	15-21-37	17-24-40	19-27-43	20-29-46	22-31-49	23-33-51	25-34-53	26-36-55
12" Oval Inlet	Airflow, CFM	300	340	380	420	460	500	540	580
	Total Pressure	.053	.068	.085	.104	.124	.147	.171	.198
	Noise Criteria	22	25	28	30	33	35	37	39
	Throw	17-24-40	19-27-43	20-29-46	22-31-49	23-33-51	25-34-53	26-36-55	27-37-57

Performance Notes:

- Throws are given at 150, 100 and 50 fpm terminal velocities under isothermal conditions.
- Total Pressure is in inches w.g..
- Noise Criteria [NC] values based on 10 dB room absorption, re 10⁻¹² watts.
- Cataloged throws are for a one-way horizontal air pattern. For divided airflow, deduce the airflow in each direction according to the number of slots, with the total airflow apportioned

between the slots. Look up throw for the airflow in each direction according to the number of slots in that direction.

- Performance data is based upon the standard **5300 Series** Model. The **5300MP** Modified Performance Series reduces the tabulated throw values by approximately 25%. Horizontal spread values are approximately 150% of the horizontal throw (T) projection values.
- Dash (–) in space indicates an Noise Criteria level of less than 15.

- Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70–2023.

Number of Slots	Ak Factor per foot	
	Supply	Return
1	.024	.039
2	.049	.078
3	.073	.117
4	.098	.156