
EQUIPMENT/VISION SCREEN
4" (102) DEEP • HORIZONTAL BLADE
MODEL: 1604ESJ

Nailor® Industries Inc.

Model 1604ESJ is a louvered equipment/vision screen that utilizes inverted J style blades crafted with a clean, continuous architectural appearance that will visually compliment any structure's exterior. The unique design serves to inhibit vision from grade or lower elevations while also serving as a protective barrier. Available in a variety of finishes to meet almost any requirement, Nailor's equipment screens are engineered to be aesthetically appealing as well as mechanically enduring.



STANDARD CONSTRUCTION:

BLADES: Type 6063-T6 extruded aluminum, .080" (2.03) nominal wall thickness.

BLADE ANGLE: Fixed at approximately 37 1/2 degrees.


BLADE SPACING: Approximately 4" (102) on centers.

BLADE SUPPORT BRACKETS: Standard 1 1/2" x 2" (38 x 51) angle with blade brace on 60" (1524) centers designed to meet 25 psf windloads. Consult factory for higher windload requirements.

FINISH: Mill.

MINIMUM SIZE: 12" W x 12" H (305 x 305).

MAXIMUM SIZE 120" W x 84" H (3048 x 2134) or 84" W x 120" H (2134 x 3048). 70 sq. ft. (6.5m²). Screens which exceed this size will be shipped in sections for field assembly. Screens will be shipped in straight sides with optional corner assembly in the field where required.



OPTIONS:


- ❑ **SBCC** Box Corner.
- ❑ **SMCC** Mitered Corner.

OPTIONAL FINISHES:


- ❑ **PC3** Powder Coat AAMA 2603. Color: _____ .
- ❑ **PC4** High Performance Powder Coat AAMA 2604 (Equivalent to 50% Kynar®). Color: _____ .
- ❑ **PC5** Fluoropolymer Powder Coat AAMA 2605 (Equivalent to 70% Kynar®). Color: _____ .
- ❑ **PCC** Prime Coat.
- ❑ **AN04** Clear Anodized 204-R1.
- ❑ **AN15** Clear Anodized 215-R1.

Color Anodized:


- ❑ **ANLB** Light Bronze.
- ❑ **ANMB** Medium Bronze.
- ❑ **ANDB** Dark Bronze.
- ❑ **ANBK** Black.



Box (Post) Corner Detail (Optional)



Continuous Line Detail



Mitered Corner Detail (Optional)

Dimensions are in inches (mm).

SCHEDULE TYPE:				
PROJECT:				
ENGINEER:	**DATE**	**B SERIES**	**SUPERSEDES**	**DRAWING NO.**
CONTRACTOR:	**8 - 24 - 15**	**1600**	**NEW**	**1604ESJ**

Nailor Industries Inc. reserves the right to change any information concerning product or pricing without notice.

Nailor® Louver Finishes & Color Guide


Slate Blue **LF01**


Medium Bronze **LF02**


Sandstone **LF03**


Light Gray **LF04**


Charcoal **LF05**


Bone White **LF06**


Western Tan **LF07**


Architectural Bronze **LF08**


Regal Blue **LF09**


Forest Green **LF10**


Surrey Beige **LF11**


Royal Brown **LF12**


Barn Red **LF13**


Burgundy **LF14**


Clay **LF15**

Almond **LF16**


Coastal White **LF17**


Vista Green **LF18**


Black **LF19**


Gloss Black **LF20**


Campus Green **LF21**

Nailor offers 21 standard paint colors selected for architectural exterior use which meet or exceed AAMA specifications and performance requirements for color retention, chalk resistance, gloss retention, erosion, corrosion and chemical resistance as well as dry film thickness and hardness. Our state-of-the-art powder coat system provides an environment friendly finishing solution with more uniform coverage and coating thickness. The result is an exceptional finish that better resists scratching, fading and general wear. Additional liquid coat facilities for special requirements complete our ability to provide unmatched beauty and durability for any application.

Custom color matching is also available upon request. Contact your local Nailor representative.

Available Finishes

FINISH TYPE	DESCRIPTION	STANDARD WARRANTY
Fluoropolymer Powder Coat AAMA 2605-Superior Finish (AKA: Powdura® 5000, Coraflon® Powder, Interpon® D3000-Fluoromax, IFS 500FP)	**"Ultimate"** - A next generation hyper durable powder coating, based on FEVE fluoropolymer resins and ceramic pigmentation that the industry has acknowledged as the foundation for superior performance coatings. They provide a hard surface that is resistant to scratching and scuffing, with superior color and gloss retention, when applied to a variety of exterior architectural applications. This technology represents the "ultimate" in environmentally friendly finishes, with Zero-VOC emissions. A superior alternative to traditional 70% Kynar 500® / Hylar 500® PVDF fluoropolymer liquid coatings.	10 years (20 years optional)
High Performance Powder Coat AAMA 2604 - High Performance Finish (AKA: Powdura® 4000, Envirocron® Ultra Durable Powder, Dynadure™ 400, Interpon® D2000, IFS 400SD)	**"Better"** - A high performance polyester powder coating, based on "super durable" resins that utilize infrared reflective pigments, which provides excellent resistance to outdoor weathering. A harder and more environmentally friendly coating than other liquid paint counterparts and with Zero-VOC emissions. A good alternative to 50% Kynar 500® / Hylar 5000® liquid coatings.	5 years
Durable Powder Coat AAMA 2603 - Pigmented Organic Coatings (AKA: Powdura® 3000, Envirocron® Durable Powder, Dynadure™ 300, Interpon® D1000, IFS 300SP)	**"Good"** - A durable powder coat based on thermosetting polyester resin technology. Provides a good economical combination of physical and chemical resistance properties. Environmentally superior to liquid spray paints and Zero – VOC emissions.	1 year
Clear Anodize 215-R1 AA-M10C22A41 (0.7 mil. min.)	Architectural Class I. Clear, colorless and hard oxide aluminum coating that resists weathering and chemical attack. Recommended for severely corrosive and abrasive atmospheric exposure.	5 years
Clear Anodize 204-R1 AA-M10C22A31 (0.4 - 0.7 mil.)	Architectural Class II. Clear, colorless and hard oxide aluminum coating that resists weathering and chemical attack. Recommended for normal weather exposure.	1 year
Color Anodize AA-M10C22A44 (0.7 mil. min.)	Architectural Class I. "Two-step" aluminum coating process. Following a standard anodizing procedure, a second electrolytic process deposits colored metallic pigments which penetrate the aluminum oxide pores, producing a corrosion resistant, colorfast finish. Available in light, medium, dark bronze and black.	5 years
Prime Coat	Prime coat provides a stable base for painting of louvers in the field. Surface pretreatment includes degreasing and a chemical cleaning before an epoxy prime coat is applied. Finish coat should be field applied as soon as possible for best adhesion, after a thorough cleaning for dust etc. that can contaminate the final finish and cause premature flaking or peeling.	N/A

Paint finish warranties are not applicable to steel products.

Powdura® is a registered trademark of The Sherwin-Williams Company.
Coraflon® and Envirocron® are registered trademarks of PPG Industries Ohio, Inc.
Interpon® is a registered trademark of Akzo Nobel Powder Coatings Ltd.
Kynar 500® is a registered trademark of Arkema, Inc.
Hylar 5000® is a registered trademark of Solvay Solexis, Inc.