


## PLENUM SLOT DIFFUSER FOR NARROW REGRESSED T-BAR CEILING SYSTEMS RETURN AIR UNIT WITH LIGHT BARRIER MODELS: 5850R-F2, 5875R-F2 AND 5810R-F2



#### **DESCRIPTION:**

- 1. The 5800R-F2 Series is designed as a matching return unit to complement the 5800-F2 Series supply unit.
- 2. The 5800R-F2 Series has been specially developed to integrate with and complement 'Fineline®' type suspended ceiling grids.

Available in 24" (600) or 48" (1200) nominal lengths to suit both imperial and metric ceiling grids. A choice of three slot widths and one, two, three or four slot configurations are available.

The single slot units are for installation alongside a main T-Bar runner. Multi-slot units incorporate factory installed 1" (25) flat face T-Bars

- 3. Light barrier blocks light from ceiling plenum and also prevents see-through.
- 4. Material: Corrosion resistant steel.
- Finish: AW Appliance White on center T-Bars. BK Black on exposed surfaces.

# SPECIFIED T-BAR: \( \text{A} \) \( \text{C} \) \( \text{D} \) \( \text{OPTIONS:} \)

- 1. 


  EX External Foil Back Insulation
- 2. Internal Insulation
  - a. Model 5850RI-F2 Model 5875RI-F2 Model 5810RI-F2
  - b. FGI 1/4" (6) Coated Fiberglass (standard)
    - ☐ FFI 3/8" (10) Fiber-free foam
- 3. ☐ CN Cross Notch. For 48" (1219) nominal length diffusers. The vast majority of ceiling systems utilize a 2' x 2' (610 x 610) grid and require this option.
  - ☐ No Cross Notch on 48" (1219) units.

### **Imperial Ceiling Modules (inches)**

| _                 | _                                |        |
|-------------------|----------------------------------|--------|
| Nominal<br>Length | Overall Plenum Length L Length P |        |
| 24                | 23 3/4                           | 23 3/8 |
| 48                | 47 3/4                           | 47 3/8 |

### **Metric Ceiling Modules (mm)**

| Nominal<br>Length | Overall<br>Length L | Plenum<br>Length P |
|-------------------|---------------------|--------------------|
| 600               | 594                 | 584                |
| 1200              | 1194                | 1184               |



| Model    | S          | Width W     |             |              |          |  |
|----------|------------|-------------|-------------|--------------|----------|--|
| Model    | Slot Width | 1 Slot      | 2 Slot      | 3 Slot       | 4 Slot   |  |
| 5850R-F2 | 1/2" (13)  | 1 1/2" (38) | 3" (76)     | 4 1/2" (114) | 6" (152) |  |
| 5875R-F2 | 3/4" (19)  | 1 3/4" (44) | 3 1/2" (89) | 5 1/4" (133) | 7" (178) |  |
| 5810R-F2 | 1" (25)    | 2" (51)     | 4" (102)    | 6" (152)     | 8" (203) |  |

| T-Bar Type (Manufacturer) |                            | Х             | Υ         |  |
|---------------------------|----------------------------|---------------|-----------|--|
| Α                         | Chicago Metallic Ultraline | 1 3/4" (44)   | 5/16" (8) |  |
| C                         | Certainteed Smoothline     | 1 5/8" (41)   | 5/16" (8) |  |
| D                         | Donn Fineline              | 1 25/32" (45) | 5/16" (8) |  |

Fineline® is a registered trademark of USG Interiors Inc.

| SCHEDULE TYPE: | Dimensions are in inches (mm).  |          |              |             |  |
|----------------|---------------------------------|----------|--------------|-------------|--|
| PROJECT:       | Differsions are in mones (min). |          |              |             |  |
| ENGINEER:      | DATE                            | B SERIES | SUPERSEDES   | DRAWING NO. |  |
| CONTRACTOR:    | 8 - 1 - 15                      | 5700     | 11 - 11 - 13 | 5800-F4     |  |