Nailor[®] Industries Inc.

PATTERN CEILING DIFFUSERS ADJUSTABLE VANES • STEEL • SQUARE OR ROUND NECK MODELS: 6550 AND 6550-0 TYPE L


TYPE L LAY-IN T-BAR

ADJUSTABLE

VANE

ADJUSTABLE

VANE



If the ceiling module is not 3" (76) or 6" (152) larger than the neck size of the diffuser in both dimensions, a module sized extended panel will be added. Minimum duct size: 6×6 (152 x 152). Maximum duct size: see table. Available in 3" (76) increments only.

> Horizontal Pattern Adjustable Vane Open Position

> > Vertical Pattern

Adjustable Vane Closed Position

	IMPERIAL	METRIC MODULES				
Imperial Units (in.)		Metric Units (mm)		Metric Units (mm)		
СМ	Maximum	CM I	Maximum	СМ	Maximum	
	Duct Size		Duct Size	GM	Duct Size	
12 x 12	6 x 6	305 x 305	152 x 152	300 x 300	152 x 152	
20 x 20	15 x 15	508 x 508	381 x 381	500 x 500	381 x 381	
24 x 12	18 x 6	610 x 305	457 x 152	600 x 300	457 x 152	
24 x 24	18 x 18	610 x 610	457 x 457	600 x 600	457 x 457	
48 x 24	18 x 18	1219 x 610	457 x 457	1200 x 600	457 x 457	

DESCRIPTION:

- 1. Material: Corrosion-resistant steel.
- 2. Model 6550 is a high capacity ceiling diffuser available with a square 4-way blow pattern as standard (optional core styles are available). The unit is supplied with independent movable vanes on all four sides to provide a horizontal to vertical throw adjustable discharge. In the horizontal setting, the diffuser provides a tight horizontal airflow pattern from maximum to minimum airflow. Ideal for VAV applications.
- 3. Spring-loaded removable core.
- 4. Standard finish is AW Appliance White.

OPTIONS:

SQUARE AND RECTANGULAR NECK

□ Steel opposed blade damper. Model 6550-O.

ROUND NECK

- SR Square to round transition collar
- SR-O Square to round transition collar for use over O.B.D.
- □ 4275 Radial Opposed Blade Damper (round)
- 4250 Radial Sliding Blade Damper (round)
- 4675 Butterfly Damper (round)

EXTERNAL INSULATION

- EX External Foil-Back Insulation, installed R-4.2.
- MIB Molded Insulation Blanket, -R-6.0. ('MIB' is available for Frame Types L, TL and F with a 24 x 24 CM only, 15 x 15 max. neck size and a 'SR' square-to-round transition collar).

OPTIONAL FINISH:

SP Special. Spec	cify
------------------	------

SCHEDULE TYPE:	Dimensions are in inches (mm).					
PROJECT:						
ENGINEER:	DATE	B SERIES	SUPERSEDES	DRAWING NO.		
CONTRACTOR:	2 - 8 - 18	6550	1 - 16 - 17	6550-3		

Nailor Industries Inc. reserves the right to change any information concerning product or pricing without notice.