

PERFORMANCE DATA:

MODEL SERIES: 45DLC SPIRAL DUCT DRUM LOUVER AND 45DL DRUM LOUVER • 6" (152)

SIZE	Neck Velocity, FPM Velocity Pressure	280 .005	420 .011	560 .020	700 .031	840 .044	980 .060	1120 .078	1400 .122	1680 .176
9 x 6	Airflow, CFM	105	158	210	263	315	368	420	525	630
	Total Pressure	.022	.06	.10	.16	.21	.30	.40	.60	.90
	Throw	7-10-18	10-14-24	13-18-30	15-21-35	17-23-40	20-28-46	22-30-50	26-35-56	30-40-66
	Noise Criteria	–	–	–	22	27	32	36	41	46
12 x 6	Airflow, CFM	140	210	280	350	420	490	560	700	840
	Total Pressure	.03	.06	.10	.16	.23	.32	.40	.63	.90
	Throw	8-11-18	12-16-27	16-21-34	18-24-40	20-26-45	23-31-50	25-34-55	30-40-66	35-47-76
	Noise Criteria	–	–	–	23	28	33	37	42	47
18 x 6	Airflow, CFM	210	315	420	525	630	735	840	1050	1260
	Total Pressure	.022	.06	.10	.16	.24	.33	.40	.60	.90
	Throw	12-16-27	17-22-36	21-27-45	25-32-52	28-37-62	31-42-70	34-46-76	42-54-90	48-62-101
	Noise Criteria	–	–	–	24	29	34	38	43	49
24 x 6	Airflow, CFM	280	420	560	700	840	980	1120	1400	1680
	Total Pressure	.03	.06	.10	.16	.24	.32	.40	.63	.90
	Throw	16-21-33	21-28-44	26-33-54	31-40-64	35-45-72	38-50-80	42-52-88	48-64-100	52-71-110
	Noise Criteria	–	–	–	26	31	36	40	47	52
30 x 6	Airflow, CFM	350	525	700	875	1050	1225	1400	1750	2100
	Total Pressure	.022	.06	.10	.16	.21	.32	.40	.63	.90
	Throw	19-24-38	25-32-50	30-38-60	35-45-70	39-50-78	43-56-86	47-60-94	54-70-100	60-78-120
	Noise Criteria	–	–	20	27	32	37	41	48	53
36 x 6	Airflow, CFM	420	630	840	1050	1260	1470	1680	2100	2520
	Total Pressure	.03	.06	.10	.16	.22	.30	.40	.60	.90
	Throw	20-26-40	26-35-54	32-41-64	36-46-74	40-52-82	44-55-90	48-62-100	54-72-115	62-80-130
	Noise Criteria	–	–	21	28	33	38	42	49	55
48 x 6	Airflow, CFM	565	848	1130	1412	1695	1978	2260	2825	3390
	Total Pressure	.03	.06	.10	.16	.24	.32	.40	.63	.90
	Throw	24-31-39	31-42-63	37-49-76	44-56-89	48-62-100	50-70-110	58-74-120	65-82-130	74-95-150
	Noise Criteria	–	–	22	29	34	39	43	50	56
60 x 6	Airflow, CFM	700	1050	1400	1750	2100	2450	2800	3500	4200
	Total Pressure	.03	.06	.10	.16	.24	.32	.40	.63	.90
	Throw	28-36-54	34-46-66	43-55-84	49-63-96	52-70-110	60-75-120	65-82-130	75-90-150	84-105-170
	Noise Criteria	–	–	23	30	35	40	44	51	57

Performance Notes:

- All pressures are in inches w.g..
- Throw values are given at 150, 100 and 50 fpm terminal velocities under isothermal conditions.
- Total pressure, throw and Noise Criteria are based on 45DL1 at 0° deflection. Correction factors for other conditions are listed in the chart.

- Noise Criteria (NC) values are based upon 10dB room absorption, re 10⁻¹² watts. Dash (–) in space indicates an Noise Criteria of less than 15.
- Data derived from tests conducted in accordance with ANSI/ASHRAE Standard 70 – 2006.

Correction Factor

Model	Deflection	TP	Throw	NC
45DL1	15°	x 1.5	x .85	+ 4
	30°	x 1.9	x .73	+ 9
45DL2	0°	x 1.3	—	—
	15°	x 1.7	x .85	+ 4
	30°	x 2.2	x .73	+ 9