

HURRICANE LOUVERS: FLORIDA PRODUCT APPROVED MIAMI-DADE QUALIFIED



FLORIDA PRODUCT APPROVED

FLORIDA PRODUCT APPROVED • MIAMI-DADE QUALIFIED

MODELS:
**1604DHPF,
1606DHPF**

MODELS:
**1605WDF,
1606WDF**

MODEL:
1605WDFV

MODEL:
1606DHPM

MODEL:
1605WDM

MODELS:
**1605WDVM,
1675WDVM**

Drainable Blade

Wind-Driven Rain Resistant

Wind-Driven Rain Resistant

Drainable Blade

Wind-Driven Rain Resistant

Wind-Driven Rain Resistant Vertical Blade

Model	FA%	Free Area Ft ² (m ²)	Water Penetration fpm (m/min)
1604DHPF	57%	9.11 (0.85)	954 (291)
1606DHPF	60%	9.65 (0.90)	1186 (361)

Model	FA%	Free Area Ft ² (m ²)	Water Penetration fpm (m/min)
1605WDF	47%	7.59 (0.71)	1250 (381)
1606WDF	47%	7.52 (0.70)	1250 (381)

Model	FA%	Free Area Ft ² (m ²)	Water Penetration fpm (m/min)
1605WDFV	55%	8.77 (0.81)	1250 (381)

Model	FA%	Free Area Ft ² (m ²)	Water Penetration fpm (m/min)
1606DHPM	60%	9.65 (0.90)	1186 (361)

Model	FA%	Free Area Ft ² (m ²)	Water Penetration fpm (m/min)
1605WDM	47%	7.59 (0.71)	1250 (381)

Model	FA%	Free Area Ft ² (m ²)	Water Penetration fpm (m/min)
1605WDVM	55%	8.77 (0.81)	1250 (381)
1675WDVM*	47%	7.57 (0.70)	1250 (381)

- AMCA Licensed
- AMCA 540/550* listed**
- High free area, low pressure drop
- Approved for wind loads up to ±150 psf (7 kPa)***
- Suitable for ventilation, exhaust and high velocity intake
- Optional flanged frame, extended sill, S. S. bird screen, aluminum or S. S. insect screen, variety of standard and high performance powder coat finishes, clear or color anodized finishes

- AMCA Licensed
- AMCA 540/550* listed**
- Approved for wind loads up to ±150 psf (7 kPa)**v
- Suitable for ventilation, exhaust and high velocity intake
- Class A Wind-Driven Rain performance
- Optional flanged frame, extended sill, S. S. bird screen, aluminum or S. S. insect screen, variety of standard and high performance powder coat finishes, clear or color anodized finishes

- AMCA Licensed
- AMCA 540/550 listed
- For wind loads up to ±130 psf (6 kPa)*
- Class A Wind-Driven Rain performance
- Optional flanged frame, extended sill, S. S. bird screen, aluminum or S. S. insect screen, variety of standard and high performance powder coat finishes, clear or color anodized finishes

- AMCA Licensed
- AMCA 540/550 listed*
- Tested in accordance TAS-100A*, TAS-201, TAS-202, TAS-203
- Approved for wind loads up to ±150 psf (7 kPa)
- Suitable for ventilation, exhaust and high velocity intake
- Optional flanged frame, extended sill, S. S. bird screen, aluminum or S. S. insect screen, variety of standard and high performance powder coat finishes, clear or color anodized finishes

- AMCA Licensed
- AMCA 540/550 listed*
- Tested in accordance TAS-100A*, TAS-201, TAS-202, TAS-203
- Approved for wind loads up to ±150 psf (7 kPa)
- Suitable for ventilation, exhaust and high velocity intake
- Optional flanged frame, extended sill, S. S. bird screen, aluminum or S. S. insect screen, variety of standard and high performance powder coat finishes, clear or color anodized finishes

- AMCA Licensed
- AMCA 540/550 listed
- Tested in accordance with TAS-100A, TAS-201, TAS-202, TAS-203
- Suitable for protecting intake and exhaust openings in exterior walls
- Class A Wind-Driven Rain performance
- Optional flanged frame, extended sill, S. S. bird screen, aluminum or S. S. insect screen, variety of standard and high performance powder coat finishes, clear or color anodized finishes

* 1606DHPF with optional Model 2020 damper in closed position
** 1604DHPF is not AMCA 550 rated
***Size and configuration dependent

* 1605WDF with optional Model 2020 damper in closed position
** 1606WDF is not AMCA 550 rated
***Size and configuration dependent

* Size and configuration dependent

* With optional Model 2020 damper in closed position

* With optional Model 2020 damper in closed position

NOTE:160(X) denotes louver depth. e.g. 1606DHPF = 6" deep.

Nailor Hurricane Louvers are designed to meet the stringent codes required by state and local governments in the hurricane prone region of the United States.

For the most up to date information, go to nailor.com